

MIRASOL™

GLAZED PORCELAIN FLOOR TILE AND GLAZED CERAMIC WALL & MOSAIC TILE

AMERICAN OLEAN®



MARBLE LOOK



AMERICAN OLEAN®

MIRASOL™

Mirasol™ is an elegant porcelain floor and glazed ceramic wall and mosaic series with the clean, classic beauty of natural marble. The color palette consists of popular marble looks and colors: Bianco Carrara, Crema Laila and Silver Marble. The floor sizes and mosaic have a soft matte finish, while the coordinating wall sizes have a glossy finish. Mirasol is an ideal option for those who desire the beauty of marble with the long-lasting durability and ease of maintenance of tile.

AMERICAN OLEAN



PROVEN IN TILE

Cover and above photos feature Mirasol Silver Marble 12 x 24 on the floor and Silver Marble 10 x 14 on the bathtub and wall.

FINISHES: MATTE | GLOSSY

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
 FLOOR  WALL  COUNTERTOP  SHOWER FLOOR  EXTERIOR FLOOR	 PG GLAZED PORCELAIN  CG GLAZED CERAMIC	 LOW  HIGH	 STEPWISE™  TRUEDGE™  REVEAL SYNC3D™  MADE IN THE U.S.A.

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MARBLE LOOK

GLAZED PORCELAIN FLOOR TILE



BIANCO CARRARA ML70



CREMA LAILA ML71



SILVER MARBLE ML72

GLAZED CERAMIC WALL TILE



BIANCO CARRARA ML70



CREMA LAILA ML71



SILVER MARBLE ML72

GLAZED CERAMIC MOSAIC



BIANCO CARRARA ML70



CREMA LAILA ML71



SILVER MARBLE ML72



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT AMERICANOLEAN.COM/WHY TILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE | GLOSSY

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
 FLOOR  WALL  COUNTERTOP  SHOWER FLOOR  EXTERIOR FLOOR	 PG GLAZED PORCELAIN  CG GLAZED CERAMIC	 LOW  HIGH	 STEPWISE™  TRUEDGE™  REVEAL SYNC3D™  MADE IN THE U.S.A.

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

		THICKNESS	FINISH	MADE IN U.S.A.
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	 M
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	 M
	12 x 12 Floor Tile	11-5/8" x 11-5/8" (29.56 cm x 29.56 cm)	5/16"	 M
	12 x 24 Wall Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	3/8"	 M  G
	2 x 4 Brick-Joint Mosaic (Dot-mounted)	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"	 M

Made in the U.S.A. designation is subject to change. Please visit americanolean.com for the most current manufacturing information. Matte Finish  Glossy Finish

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior Floor	N/A	 *
Wet & Level - Interior Floor	≥ 0.42	 *
Shower Floors - Standard Center Drain	≥ 0.42	 **
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	 ** 
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	 *
Countertops	N/A	 *
Pool Linings	N/A	 **

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:
Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.
Wall and mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Floor and mosaic tile only.
** Mosaic tile only.

FEATURES


 PRE-CONSUMER RECYCLED MATERIALS	 POST-CONSUMER RECYCLED MATERIALS
 REVEAL IMAGING®	



ZEROTOX

All or select items within this series meet the requirements for these qualifications.
For more information visit americanolean.com.

SPECIAL FEATURES



MARBLE LOOK

TRIM

	NUMBER	FINISH
	3 x 12	S43C9  M  G
	3 x 12	S43C9WX  M  G
	3 x 3	SN43C9WX  M  G

 Matte Finish  Glossy Finish

INSTALLATION

Grout Joint Recommendation

Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%).

Wall Tile: (12 x 24) 1/8" 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) (10 x 14) 1/16"

Mosaic Tile: 1/8"

Shade Variation



PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	<20.0%	<3.0%
Breaking Strength	C648	> 275 lbf	≥ 125 lbf	>250 lbf
Scratch Hardness	C1895	8.0	≥ 4.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	4 All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.



AMERICAN OLEAN®