

MYTHIQUE MARBLE™ & MICROBAN®

PROTECTION THAT LIVES ON

COLORBODY™ PORCELAIN & GLAZED PORCELAIN FLOOR
AND GLAZED CERAMIC WALL & MOSAIC

AMERICAN OLEAN®



MARBLE LOOK



AMERICAN OLEAN®
PROVEN IN TILE™

MYTHIQUE MARBLE™ & MICROBAN®

PROTECTION THAT LIVES ON



Strikingly elegant and notably durable – Mythique Marble™ features proprietary Microban® Technology offering a lifetime of built-in antimicrobial product protection that does not wash off or wear away. Radiating with endless design possibilities – the magic of this collection comes alive with exquisite marble inspired visuals, a variety of sizes for floor and wall, as well as two different finishes. For a final touch of refined detail – a stunning arabesque mosaic and an 8" Hexagon beautifully complete the collection.

THE ALFORD — BOUTIQUE & SPA —



Cover photo features Majestic, 12 x 24 on the floor.

Above photo features Botticino 8" Hexagon on the wall and 12 x 24 on the floor.

FINISHES: MATTE | POLISHED


USAGE




MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MARBLE LOOK

COLORBODY™ PORCELAIN FLOOR TILE



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12

GLAZED CERAMIC WALL TILE



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12


GLAZED CERAMIC MULTI-WAVE CREST WALL TILE



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12

GLAZED PORCELAIN 8" HEXAGON FLOOR TILE



CALACATTA
VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13




MAJESTIC MY12

GLAZED CERAMIC ARABESQUE MOSAIC TILE 11" X 12" SHEET



CALACATTA
VENECIA MY15



ALTISSIMO MY14



BOTTICINO MY17



MAJESTIC MY16

JOLLY TRIM



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™
Applicable to products with Matte and
Textured finishes



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE | POLISHED

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			THICKNESS	FINISH	MADE IN U.S.A.
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	M P	
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	M P	
	12 x 12 Floor Tile	11-5/8" x 11-5/8" (29.56 cm x 29.56 cm)	5/16"	M P	
	8" Hexagon Floor Tile	7-7/8" x 7-15/16" (19.95 cm x 23.04 cm)	5/16"	M	
	3 x 12 Wall Tile	3" x 12" (7.65 cm x 30.70 cm)	5/16"	M	
	8 x 24 Wall Tile	7-3/4" x 23-3/4" (19.75 cm x 60.42 cm)	3/8"	M	
	8 x 24 Multi-Wave Crest Wall Tile	7-3/4" x 23-3/4" (19.75 cm x 60.42 cm)	3/8"	M	
	Arabesque Mosaic Tile (Dot-mounted)	11" x 12" Sheet (27.94 cm x 30.48 cm Sheet)	1/4"	M	

M Matte Finish P Polished Finish NOTE: Microban® Technology is available in floor and wall tile only.

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior Floor	N/A	*
Wet & Level - Interior Floor	≥ 0.42	**
Shower Floors - Standard Center Drain	≥ 0.42	***
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	***
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●***

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, (provided it is noted as suitable in the applications chart above) when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications in non-freezing climates, (provided it is noted as suitable in the applications chart above) when proper installation methods are followed.

* Floor and mosaic tile only

** Matte floor and mosaic tile only

*** Mosaic tile only

FEATURES



ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

MARBLE LOOK

TRIM

			NUMBER	FINISH
	Floor Bullnose	3 x 12	P43C9	M
	Jolly*	1/2 x 12	S1/212J	M

M Matte Finish

* Microban not included

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.) 8" Hex Floor Tile: 3/16" Wall Tile: (6 x 18) 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.) (4 x 12) 1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.) Mosaic Tile: 1/8"	 HIGH (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	<20.0%	<3.0%
Breaking Strength	C648	> 275 lbf	120 - 230 lbf	>250 lbf
Scratch Hardness	C1895	6.0 (Polished) 8.0 (Matte)	4.0 - 6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	4 All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

888.AOT.TILE



AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

©2025 AMERICAN OLEAN (05/25)