



COLORBODY™ PORCELAIN FLOOR* AND GLAZED CERAMIC WALL & MOSAIC

FLOOR | WALL

MARBLE LOOK



*Hex is Glazed Porcelain



MYTHIQUE MARBLE™ & MICROBAN®

PROTECTION THAT LIVES ON



Strikingly elegant and notably durable – Mythique Marble™ features proprietary Microban® Technology offering a lifetime of built-in antimicrobial product protection that does not wash off or wear away. Designed to promote cleaner spaces empowered with Microban® antimicrobial product protection for your floor, wall and mosaic tile. Radiating with endless design possibilities – the magic of this collection comes alive with exquisite marble inspired visuals, a variety of sizes for floor and wall, as well as two different finishes. For a final touch of refined detail – a stunning arabesque mosaic and an 8" Hexagon beautifully complete the collection.



COVER PHOTO: CALACATTA VENEZIA
ABOVE PHOTO: MAJESTIC

FLOOR | WALL

FINISHES: MATTE | POLISHED

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



MARBLE LOOK

COLORBODY™ PORCELAIN FLOOR TILE (AVAILABLE IN MATTE & POLISHED)



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12

GLAZED CERAMIC WALL TILE - MATTE



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12


GLAZED CERAMIC MULTI-WAVE CREST WALL TILE - MATTE



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12

GLAZED PORCELAIN 8" HEXAGON FLOOR TILE - MATTE^o



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12

GLAZED CERAMIC ARABESQUE MOSAIC 11" X 12" SHEET - MATTE



CALACATTA VENECIA MY15



ALTISSIMO MY14



BOTTICINO MY17



MAJESTIC MY16

JOLLY TRIM



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT[†]



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

[†]Hex is Glazed Porcelain
^oMicroban not included

FLOOR | WALL

FINISHES: MATTE | POLISHED

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



MARBLE LOOK

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	15.20	4
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	16.83	9
	12 x 12 Floor Tile	11-5/8" x 11-5/8" (29.56 cm x 29.56 cm)	5/16"	12.22	13
	8" Hexagon Floor Tile ^{◇*}	7-7/8" x 9-1/8" (20.04 cm x 23.16 cm)	5/16"	9.37	25
	3 x 12 Wall Tile [‡]	3" x 12" (7.65 cm x 30.70 cm)	5/16"	12.00	48
	8 x 24 Wall Tile [‡]	7-3/4" x 23-3/4" (19.75 cm x 60.42 cm)	3/8"	12.80	10
	8 x 24 Multi-Wave Crest Wall Tile [‡]	7-3/4" x 23-3/4" (19.75 cm x 60.42 cm)	3/8"	12.80	10
	Arabesque Mosaic [^]	11" x 12" Sheet (27.94 cm x 30.48 cm sheet)	1/4"	7.40	10

‡ Only available in Matte ^ Dot-mounted ◇ Microban not included * Hex is Glazed Porcelain

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	● [†]
Wet & Level – Interior Floor	≥ 0.42	● ^{**†}
Shower Floors (Residential or Light Commercial)	≥ 0.42	● ^{**}
Exterior Floor Applications (Including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	● [†]
Pool Linings	N/A	● ^{**}

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Wall tile and mosaics suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

- * Matte only
- ** Mosaic tile only
- † Wall Tile not suitable for this application.

FEATURES



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.
[†]Hex is Glazed Porcelain

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 24	P43F9	10
	Jolly [‡]	1/2 x 12	S1/212J	6 CARDS*

*4 pieces per card ◇ Microban not included

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>Floor: 1/8"</p> <p>(3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)</p> <p>Wall: 8 x 24 1/16"</p> <p>(1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)</p> <p>3 x 12 1/16"</p> <p>(When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)</p> <p>Mosaic: 1/8"</p>	<p>High (V3) (MY10, MY11, MY13, MY14, MY15, MY17)</p> <p>Random (V4) (MY12, MY16)</p>

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	<20.0%	<3.0%
Breaking Strength	C648	> 275 lbs	120 - 230 lbs	>250 lbs
Scratch Hardness	MOHS	6.0(Polished) 8.0(Matte)	4.0 - 6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.