

MYTHIQUE MARBLE™ & **MICROBAN®**

COLORBODY™ & GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC MOSAIC

PROTECTION THAT LIVES ON 

AMERICAN OLEAN®



MARBLE LOOK



AMERICAN OLEAN®

MYTHIQUE MARBLE™ & MICROBAN®

PROTECTION THAT LIVES ON 

Strikingly elegant and notably durable – Mythique Marble™ features proprietary Microban® Technology offering a lifetime of built-in antimicrobial product protection that does not wash off or wear away. Radiating with endless design possibilities – the magic of this collection comes alive with exquisite marble inspired visuals, a variety of sizes for floor, as well as two different finishes.

For a final touch of refined detail – a stunning arabesque mosaic and an 8" Hexagon beautifully complete the collection.

THE ALFOR
— BOUTIQUE & SPA —



AMERICAN OLEAN



PROVEN IN TILE

Cover photo features Majestic, 12 x 24 on the floor.

Above photo features Botticino 8" Hexagon on the wall and 12 x 24 on the floor.

FINISHES: MATTE | POLISHED

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
FLOOR WALL COUNTERTOP SHOWER FLOOR EXTERIOR FLOOR	PC COLORBODY™ PORCELAIN PG GLAZED PORCELAIN CG GLAZED CERAMIC	LOW HIGH	STEPWISE™ TRUEEDGE® 3D REVEAL MADE IN THE U.S.A. LARGE FORMAT MOSAIC/DECO ENCAUSTIC TERRAZZO PAVER CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MARBLE LOOK

COLORBODY™ PORCELAIN FLOOR TILE



CALACATTA VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12

**GLAZED PORCELAIN
8" HEXAGON FLOOR TILE**



CALACATTA
VENECIA MY11



ALTISSIMO MY10



BOTTICINO MY13



MAJESTIC MY12

**GLAZED CERAMIC ARABESQUE MOSAIC TILE
11" X 12" SHEET**



CALACATTA
VENECIA MY15



ALTISSIMO MY14



BOTTICINO MY17



MAJESTIC MY16



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT[®]
Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT



CLIMATEPRO[®]



SIMPLICLEAN[™]

FINISHES: MATTE | POLISHED

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
 FLOOR  WALL  COUNTERTOP  SHOWER FLOOR  EXTERIOR FLOOR	 COLORBODY™ PORCELAIN  GLAZED PORCELAIN  GLAZED CERAMIC	 LOW  HIGH	 STEPWISE™  TRUEEDGE®  REVEAL SYNC3D™  MADE IN THE U.S.A.  LARGE FORMAT  MOSAIC/ DECO  ENCAUSTIC  TERRAZZO  PAVER  CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

		THICKNESS	FINISH	MADE IN U.S.A.
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"  	
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"  	
	12 x 12 Floor Tile	11-5/8" x 11-5/8" (29.56 cm x 29.56 cm)	5/16"  	
	8" Hexagon Floor Tile	7-7/8" x 7-15/16" (19.95 cm x 23.04 cm)	5/16" 	
	Arabesque Mosaic Tile (Dot-mounted)	11" x 12" Sheet (27.94 cm x 30.48 cm Sheet)	1/4" 	

Made in the U.S.A. designation is subject to change. Please visit americanolean.com for the most current manufacturing information.

 Matte Finish  Polished Finish NOTE: Microban® Technology is available in floor only.

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	 *
Shower Floors - Standard Center Drain	≥ 0.42	 **
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	 **
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:
Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Matte floor and mosaic tile only.

** Mosaic tile only.

FEATURES

 PRE-CONSUMER RECYCLED MATERIALS

 POST-CONSUMER RECYCLED MATERIALS

 REVEAL IMAGING®

 CERTIFIED PORCELAIN TILE
0.6% or less water absorption

 GREEN BUILDING COUNCIL MEMBER

ZEROTOX

All or select items within this series meet the requirements for these qualifications.
For more information visit americanolean.com.

MARBLE LOOK

TRIM

	NUMBER	FINISH
	3 x 12	P43C9  

 Matte Finish  Polished Finish

* Microban not included

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%). 8" Hex Floor Tile: 3/16" Mosaic Tile: 1/8"	 HIGH (V3)

PERFORMANCE CHARACTERISTICS

ASTM#	FLOOR RESULT	MOSAIC RESULT
Water Absorption	< 0.5%	<3.0%
Breaking Strength	> 275 lbf	>250 lbf
Scratch Hardness	6.0 (Polished) 8.0 (Matte)	7.0
Chemical Resistance	Resistant	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	4 All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

888.AOT.TILE

AMERICANOLEAN.COM

©2026 AMERICAN OLEAN (1/26)