

PLAYSCAPES™

GLAZED CERAMIC WALL

AMERICAN OLEAN®



WALL



AMERICAN OLEAN®

PLAYSCAPES™

Inspired by mid-century modernism, Playscapes™ showcases a lively array of unique wall tile shapes. Each piece has a translucent glaze with an undulated surface mimicking a handcrafted structure. Four tasteful hues, designed for delicate spaces. Three different shapes – a 6" Arabesque, 4" Hexagon, and a 3 x 6 Harlequin embody their own sense of style, perfect for building your personal design aesthetic.



Cover features Playscapes™ Meringue, Linene and Silverside 4" Hexagon on the wall and Primestone™ Ash, 12 x 24 on the floor.
Above photo features Midnight Blue 4" Hexagon on the backsplash.

FINISHES: GLOSSY

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
 FLOOR  WALL  COUNTERTOP  SHOWER FLOOR  EXTERIOR FLOOR			 STEPWISE™  TRUEDGE™  REVEAL SYNC3D™  MADE IN THE U.S.A.  LARGE FORMAT  MOSAIC/ DECO  ENCAUSTIC  TERRAZZO  PAVER  CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

WALL

6" ARABESQUE WALL TILE



MERINGUE PS70



LINEN PS72



SILVERSIDE PS73



MIDNIGHT BLUE PS76

4" HEXAGON WALL TILE



MERINGUE PS70



LINEN PS72



SILVERSIDE PS73



MIDNIGHT BLUE PS76

3x6 HARLEQUIN WALL TILE



MERINGUE PS70



LINEN PS72



SILVERSIDE PS73



MIDNIGHT BLUE PS76



STAINPROOF



DENTPROOF



FIRE-RESISTANT



SIMPICLEAN™

VISIT AMERICANOLEAN.COM/WHY TILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: GLOSSY

USAGE	FLOOR	WALL	COUNTERTOP	SHOWER FLOOR	EXTERIOR FLOOR	MATERIAL	CG GLAZED CERAMIC	PRICING	LOW	HIGH	SPECIAL FEATURES
											STEPWISE™, TRUEDGE™, REVEAL SYNC3D™, MADE IN THE U.S.A., LARGE FORMAT, MOSAIC/DECO, ENCAUSTIC, TERRAZZO, PAVER, CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

		THICKNESS	FINISH
	6" Arabesque Wall Tile	5-1/4" x 6" (13.33 cm x 15.24 cm)	5/16" 
	4" Hexagon Wall Tile	4-1/4" x 4-7/8" (10.88 cm x 12.57 cm)	5/16" 
	3 x 6 Harlequin Wall Tile	3" x 6" (7.61 cm x 15.31 cm)	5/16" 

 Glossy Finish

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors - Standard Center Drain	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A 	
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

FEATURES

	PRE-CONSUMER RECYCLED MATERIALS		POST-CONSUMER RECYCLED MATERIALS
--	------------------------------------	---	-------------------------------------



ZEROTOX

All or select items within this series meet the requirements for these qualifications.
For more information visit americanolean.com.

WALL

TRIM

	NUMBER	FINISH
	1/2 x 12	S1/212J 

 Glossy Finish

INSTALLATION

Grout Joint Recommendation	Shade Variation
	 MEDIUM (V2)

PERFORMANCE CHARACTERISTICS

ASTM#	RESULT
Water Absorption	< 20.0%
Breaking Strength	120 - 230 lbf
Scratch Hardness	4.0 - 6.0
Chemical Resistance	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	 All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

888.AOT.TILE



AMERICAN OLEAN®