

FINISHES: MATTE | TEXTURED

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



QUARRY

SHADOW GRAY 0N46

ABRASIVE SURFACE




SHADOW GRAY 0N46 (2)

SMOOTH SURFACE



SHADOW GRAY 0N46 (2)

FLASH



SHADOW FLASH 0N56 (2)


SIZES:



FINISHES: MATTE | TEXTURED

LAVA RED 0N01

ABRASIVE SURFACE



LAVA RED 0N01 (1)

SMOOTH SURFACE



LAVA RED 0N01 (1)

FLASH



FIRE FLASH 0N02 (1)

SIZES:



FINISHES: MATTE | TEXTURED

CRIMSON RED QR50

ABRASIVE SURFACE



CRIMSON RED QR50 (1)

SMOOTH SURFACE



CRIMSON RED QR50 (1)

SIZES:



FINISHES: MATTE | TEXTURED



VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE | TEXTURED

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



QUARRY

SIZES

			THICKNESS	FINISH	MADE IN U.S.A.
	8 x 8 Floor Tile	8" x 8" (20.30 cm x 20.30 cm)	1/2"	M T	
	6 x 6 Floor Tile	6" x 6" (15.20 cm x 15.20 cm)	1/2"	M T	

Made in the U.S.A. designation is subject to change. Please visit americanolean.com for the most current manufacturing information.

M Matte Finish **T** Textured Finish

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●*
Wet & Level – Interior Floor	≥ 0.42	●*
Shower Floors - Standard Center Drain	≥ 0.42	●**
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	●**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	●
Ramps & Inclines	≥ 0.65	●*
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●**

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Suitable for industrial installations requiring high compressive strength.

Subject to Oils: Absorbs oils, grease and other liquids to keep floors slip-resistant, yet does not contaminate the surface. Proper cleaning methods easily remove any contaminants that do get absorbed into the tile.

* Abrasive surface only

** 6 x 6 floor tile only

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

TRIM

			NUMBER	FINISH
	Floor Bullnose [■]	6 x 6	Q1665	M
	Floor Bullnose Corner [■]	6 x 6	QCRL1665	M
	Floor Bullnose [■]	8 x 8	Q1885	M
	Floor Bullnose Corner [■]	8 x 8	QCRL1885	M
	Cove Base*	5 x 8	Q3585	M
	Cove Base*	5 x 6	Q3565	M
	Cove Base Outcorner Right*	5 x 6	QCR3565	M
	Cove Base Outcorner Left*	5 x 6	QCL3565	M
	Cove Base Incorner*	1 x 5	QB3565	M

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

M Matte Finish

■ Available in smooth and flash

* Available in smooth finish only

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/8"	

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 3.0%
Breaking Strength	C648	> 400 lbf
Scratch Hardness	C1895	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Abrasive surface suitable for use on ramps.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special care should be taken when grouting; a grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface.

It is necessary to follow the proper procedures and recommendations for the grout and maintenance products' manufactures.

PRE-CONSUMER RECYCLED MATERIALS



ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.



888.AOT.TILE



AMERICAN OLEAN®