

THEORETICAL BOLD™

COLORBODY™ PORCELAIN FLOOR WITH REVEAL IMAGING®

AMERICAN OLEAN®



STONE LOOK



EXIT



AMERICAN OLEAN®
PROVEN IN TILE™

THEORETICAL BOLD™

Theoretical Bold™ by American Olean® makes a splash in right, spirited colors. Designed to complement the existing Theoretical™ series, this collection features the same light graphic variation for visual depth and richness, and can be used on floors or walls for an eye-catching pop of color. Available in six standout hues, Theoretical Bold is sure to turn heads.



Cover photo features Theoretical Bold™ Formula Blue 12 x 24 and Theoretical™ Ideal Beige 12 x 24 on the floor and wall, with Theoretical Creative Gray 2 x 2 mosaic on the floor.

Above photo features Theoretical Bold™ Formula Blue 12 x 24 and Theoretical™ Ideal Beige 12 x 24 on the wall.

THEORETICAL BOLD™

COLORBODY™ PORCELAIN FLOOR WITH REVEAL IMAGING®

AMERICAN OLEAN®



FINISHES: MATTE

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR




EXTERIOR FLOOR

MATERIAL



COLORBODY PORCELAIN

PRICING



LOW HIGH

SPECIAL FEATURES



MADE IN THE U.S.A.



LARGE FORMAT



TRUEEDGE™

STONE LOOK

COLORBODY™ PORCELAIN FLOOR TILE



PRIMARY YELLOW TH84



AUTHENTIC ORANGE TH88



ACADEMIC RED TH89



FORMULA BLUE TH86



GENUINE GREEN TH85



ELECTRIC BLUE TH87

THEORETICAL BOLD™

COLORBODY™ PORCELAIN FLOOR WITH REVEAL IMAGING®

AMERICAN OLEAN®

FINISHES: MATTE


USAGE




MATERIAL



PRICING



SPECIAL FEATURES



SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	12 x 24 Floor Tile	(11-5/8" x 23-3/8") (29.56 cm x 59.44 cm)	5/16"	15.12	8

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

FEATURES



PRE-CONSUMER
RECYCLED CONTENT



MADE IN THE U.S.A.



REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.



CERTIFIED
PORCELAIN™
TILE
0.2% OF DRY WEIGHT WATER ABSORPTION

888.AOT.TILE

AMERICANOLEAN.COM



AMERICAN OLEAN®
PROVEN IN TILE™

©2022 AMERICAN OLEAN (02/22)



LEARN MORE

STONE LOOK

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	P43C9	30
	Cove Base □	6 x 12	P36C9TB	22
	Cove Base Outcorner □	1 x 6	PC36C9TB	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position. Cove base and cove corner trim are suitable for non-freezing climates only.
□ Ceramic body

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.