

VISUAL IMPRESSIONS™

GLAZED CERMAIC WALL TILE

AMERICAN OLEAN®



WALL



AMERICAN OLEAN®

VISUAL IMPRESSIONS™

Create a masterpiece with the artistic edge of Visual Impressions, a contemporary and fashionable wall tile. Neutral colors and 3D patterns produce stunning works of art that you can feel, and integrate seamlessly thanks to large-format sizes with TruEdge™. Complete your look with coordinating jolly trim for a complementary, on-trend design.



Cover photo features Visual Impressions™ Quadrangle White, 8 x 24 on the wall and Creekwood™ Walnut Brook, 6 x 36 on the floor.
Above photo features Visual Impressions™ Linear Diamond White, 8 x 24 on the wall.

VISUAL IMPRESSIONS™

GLAZED CERAMIC WALL TILE

AMERICAN OLEAN®

FINISHES: MATTE | TEXTURED

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR

MATERIAL



CG
GLAZED CERAMIC

PRICING



LOW HIGH

SPECIAL FEATURES



STEPWISE™



TRUE EDGE™



REVEAL SYNC3D™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER




CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

WALL

GLAZED CERAMIC WALL TILE

FLAT



WHITE V110

LINEAR DIAMOND



WHITE V110

QUADRANGLE



WHITE V110

MULTI-WAVE



WHITE V110

JOLLY TRIM



WHITE V110



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



SIMPLICLEAN™

VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

VISUAL IMPRESSIONS™

GLAZED CERAMIC WALL TILE

AMERICAN OLEAN®

FINISHES: MATTE | TEXTURED

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			THICKNESS	FINISH
	8 x 24 Flat Wall Tile	7-3/8" x 23-3/4" (19.75 cm x 60.42 cm)	3/8"	M
	8 x 24 Textured Wall Tile	7-3/8" x 23-3/4" (19.75 cm x 60.42 cm)	3/8"	M T

M Matte Finish T Textured Finish

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors - Standard Center Drain	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

FEATURES



PRE-CONSUMER RECYCLED MATERIALS



POST-CONSUMER RECYCLED MATERIALS



ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

WALL

TRIM

			NUMBER	FINISH
	Jolly	1/2 x 12	SI/212J	M

M Matte Finish

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)	 LOW (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	RESULT
Water Absorption	C373	<20.0%
Breaking Strength	C648	≥125 lbf
Scratch Hardness	C1895	≥4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

LRV CHARACTERISTICS

	ILLUMINATE - OBS: F02-02 (CWF)
V110	72.1

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

888.AOT.TILE



AMERICAN OLEAN®