



WALL

AESTHETIC™
GLAZED CERAMIC WALL TILE



 daltile®

AESTHETIC™

GLAZED CERAMIC WALL TILE

Create striking dimension in your space with Aesthetic™. With patterns ranging from organic, natural visuals to structured, geometric textures, this large format 12x36 wall tile is designed to flow seamlessly from tile to tile. Available in a simple yet rich and elegant white, the structure is sure to be the focal point of your space.



Cover and above photo features Aesthetic™ Geometric 12 x 36 on the wall and Famed™ Luxe 12 x 24 on the floor.

WALL

USAGE



LOW HIGH

SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES:




FINISHES: MATTE | GLOSSY



FREQUENCY AS22 – SATIN



GEOMETRIC AS23 – SATIN



FLAT AS20 – SATIN
FLAT AS21 – GLOSSY



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



SIMPLICLEAN™

SIZES

	Thickness	Finish
 12 x 36 Wall Tile	AS23: 7/16"	 
	AS22: 1/2"	
	AS20 & AS21: 3/8"	
11-13/16" x 35-1/2" (30.00 cm x 90.20 cm)		

M Matte Finish - AS20, AS22 & AS23 **G** Glossy Finish - AS21

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic)	
	≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)	 Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	> 120 lbf
Scratch Hardness	C1895	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



ZEROTOX

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



©2025 Daltile (12/25)