

ARTEFINO™ VINTAGE

GLAZED PORCELAIN





Floret Mosaic



Pyramid Mosaic



Scale Mosaic



Pencil Mosaic

FINISHES: GLOSSY

2 X 6 FISH SCALE MOSAIC















1 X 6 PENCIL MOSAIC
















1/2 X 6 PYRAMID MOSAIC







SAFFRON AR46





2" FLORET MOSAIC











ANGELITE AR48











ARTEFINO™ VINTAGE

GLAZED PORCELAIN

SIZES

		Thickness	Finish
2" Floret Mosaic (Mesh-mounted)	(11-3/4" x 11-3/4" Sheet) (29.79 cm x 29.79 cm Sheet)	3/8"	G
2 x 6 Fish Scale Mosaic (Mesh-mounted)	(12-15/16" x 12-5/8" Sheet) (32.89 cm x 32.10 cm Sheet)	1/4"	G
1 x 6 Pencil Mosaic (Mesh-mounted)	(11-13/16" x 11-5/8" Sheet) (30.00 cm x 29.59 cm Sheet)	5/16"	G
1/2 x 6 Pyramid Mosaic (Mesh-mounted)	(12" x 11-3/4" Sheet) (30.40 cm x 29.79 cm Sheet)	5/16"	G



PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 5.0%
Breaking Strength	C648	>250 lbs
Scratch Hardness	C1895	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	~
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	High (V3)

NOTES

Since there are variations in all fired ceramic and natural products, tileand trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.







