



WALL

ARTIGIANO™
GLAZED CERAMIC WALL TILE



 dalTile®

ARTIGIANO™

GLAZED CERAMIC WALL TILE

Enjoy the Charm of Handcrafted Style

Inspired by the homes of southern Europe, Artigiano brings artisan appeal into any room. Its glossy, hand-painted appearance and irregular edges add to its rich, old-world look. Offered in a variety of earthy, neutral colors and two linear sizes, this resurgent design adds subtle charm to wall designs.

WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



REVEAL SYNC3D™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER




CUSTOMIZE



LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS.

SPECIAL FEATURES



Cover photo feature Artigiano™ Italian Alps 3 x 12 wall tile on the wall.
Above photo features Roman Skyline, 3 x 12 on the wall.

SIZES:



FINISHES: GLOSSY

WALL TILE



ITALIAN ALPS AR93



TREMITI SAND AR94



VENICE STATUE AR96



ROMAN SKYLINE AR98



ITALIAN ALPS AR93



TREMITI SAND AR94



VENICE STATUE AR96



ROMAN SKYLINE AR98



STAINPROOF



DENTPROOF



FIRE-RESISTANT



SIMPLICLEAN™

ARTIGIANO™

GLAZED CERAMIC WALL TILE

WALL

SIZES

			Thickness	Finish
	3 x 12 Wall Tile	2-15/16" x 11-3/4" (7.50 cm x 30.00 cm)	5/16"	G
	3 x 6 Wall Tile	2-15/16" x 5-7/8" (7.50 cm x 15.00 cm)	5/16"	G

G Glossy Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

LRV

Color #	LRV Illuminate-OBS: F02-02 (CWF)
AR93	85.3
AR94	43.0
AR96	19.4
AR98	34.9

TRIM

Type	Number	Size	Finish
 Bullnose	S4369	3 x 6	G

G Glossy Finish

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	≥ 125lbf
Scratch Hardness	C1895	≥ 4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.



ZEROTOX

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltille.com.

 **daltile®**

©2025 Daltile (12/25)