



STONE LOOK

ASTRONOMY™ +



50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to the leading MGS SpecGrade

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY



 dalTile®

ASTRONOMY™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

Cosmic Design

Inspired by a view into deep space, this porcelain tile represents the crossroads of practicality and dreams. Sprinkled with stardust, Astronomy features ColorBody™ Porcelain and StepWise™ technologies in a matte limestone look. The three mystical tones are available in your favorite sizes.

STONE
LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER
FLOOR



EXTERIOR
FLOOR



STEPWISE™



TRU-EDGE™



REVEAL
SYNC3D™



MADE IN
THE U.S.A.



LARGE
FORMAT



MOSAIC/
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



PC
COLLABORATION



LOW HIGH

SPECIAL FEATURES

SEE CHARTS FOR FULL
PRODUCT DETAILS.



Cover and above photo feature Astronomy™ Orion 12 x 24 on the floor with Panoramic Gypsum Calacatta and Chromium matte on the countertops and Gypsum Calacatta glossy on the wall.

STONE LOOK

ASTRONOMY™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

SIZES:

12 x 24
Floor Tile

6 x 24
Floor Tile

FINISHES: MATTE

COLORBODY™ PORCELAIN FLOOR TILE WITH STEPWISE™ TECHNOLOGY



ORION AT71



SOLSTICE AT72



NEBULA AT73

50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



INDOOR/OUTDOOR



SIMPLICLEAN™







VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

ASTRONOMY™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

STONE LOOK

SIZES

			Thickness	Finish	Made in U.S.A.
	12 x 24 Floor Tile	11-7/8" x 23-5/8" (30.23 cm x 60.12 cm)	5/16"		
	6 x 24 Floor Tile*	5-3/4" x 23-3/8" (14.60 cm x 59.44 cm)	5/16"		

Made in the U.S.A. designation is subject to change. Please visit daltile.com for the most current manufacturing information.

 Matte Finish

*6 x 24 floor tile available in Linear Options Program only.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic)	
	≥ 0.60 (Floor)	✓
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.







Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

TRIM

	Type	Number	Size	Finish
	Bullnose	P43F9	3 x 24	
	Cove Base	P36C9	6 x 12	
	Cove Base Outcorner	PC36C9	1 x 6	

 Matte Finish

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

Cove base and cove corner trim are suitable for non-freezing climates only.

INSTALLATION

Grout Joint Recommendation

Shade Variation

3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8,0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



ZEROTOX 

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



©2026 Daltile (05/26)