



STONE LOOK

BRYNE™

GLAZED PORCELAIN FLOOR TILE AND GLAZED CERAMIC WALL TILE & MOSAICS



 **daltile®**
IMAGINE WHAT'S POSSIBLE™

BRYNE™

GLAZED PORCELAIN FLOOR TILE AND GLAZED CERAMIC WALL TILE & MOSAICS

Inspired by the Cardoso Stone of Tuscany, escape to Italy with the wave-like movement of Bryne. Tiny crystal speckles in the soft veining create a subtle shimmer in this stone look porcelain tile. Accompany the alluring gray hues with a fluted structure for the wall to add dimension and texture or take it back to basics with a classic matte finish on the porcelain floor tile. Complementary mosaics complete this series as a full design package.



Cover photo features Bryne™ Coastline, 12 x 24 fluted wall tile on the wall and Mist, 24 x 24 matte on the floor.

Above photo features Bryne™ Mist, 1 x 6 mosaic matte on the wall, Panoramic Porcelain Surfaces™, Elemental Selection, Opal Travertine surrounding the sinks, and Anders™ Shadow 32 x 32 matte on the floor.

STONE LOOK

USAGE



SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES



FINISHES: MATTE | SATIN

GLAZED PORCELAIN FLOOR TILE



COASTLINE BR30



MIST BR31

GLAZED CERAMIC WALL TILE



COASTLINE BR30



MIST BR31

GLAZED CERAMIC 2 x 2 MOSAIC




COASTLINE BR30



MIST BR31

GLAZED CERAMIC 1 x 6 MOSAIC



COASTLINE BR30



MIST BR31



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Floor Tile	(23-13/16" x 23-13/16") (60.48 cm x 60.48 cm)	5/16"	15.76	4
	12 x 24 Floor Tile	(11-7/8" x 23-5/8") (30.23 cm x 60.12 cm)	5/16"	17.60	9
	12 x 24 Fluted Wall Tile*†	(11-3/4" x 23-3/4") (29.92 cm x 60.43 cm)	5/16"	15.56	8
	1 x 6 Mosaic (Dot-mounted)	(11-1/2" x 9-3/4" Sheet) (30.48 cm x 25.40 cm)	5/16"	8.30	10
	2 x 2 Mosaic (Dot-mounted)	(12" x 24" Sheet) (30.48 cm x 60.96 cm)	1/4"	24.00	12

* TRU-EDGE™ applies to Wall Tile only.
† Wall Tile available in Satin finish only.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓*
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓*
Pool Linings	N/A	✓**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES :

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior application (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Floor and Mosaic tile only
** Mosaic tile only

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	2 x 2 Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs	120 - 230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0 - 6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.



TRIM

Type	Number	Size	Pieces/ Carton
 Bullnose	P43F9	3 x 24	10
 Jolly†	S1/212J	1/2 x 12	12

† Jolly available in Satin finish only.

INSTALLATION

Grout Joint Recommendation

Shade Variation

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.)

 Medium (V2)

Wall: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)

Mosaic: 1/8"

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a white latex modified thin-set is recommended for installation.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.



©2023 Daltile (1/23)