



STONE LOOK

PROTECTION THAT LIVES ON 
CALLIGO™ + MICROBAN®

GLAZED PORCELAIN FLOOR TILE AND GLAZED CERAMIC WALL AND MOSAIC TILE
with MICROBAN® TECHNOLOGY



 **daltile®**
IMAGINE WHAT'S POSSIBLE™

CALLIGO™ + MICROBAN®

PROTECTION THAT LIVES ON



GLAZED PORCELAIN FLOOR TILE AND GLAZED CERAMIC WALL AND MOSAIC TILE
with MICROBAN® TECHNOLOGY

Inspired by travertine stone, Calligo embodies the natural essence of stone with the convenience and longevity of tile. Create a dimensional environment with the 12 x 24 Fluted wall tile, which introduces a play of light and shadow, while the 15 x 30 floor tile and the 1 x 6 mosaic provide a modern backdrop to any space. Build lasting confidence with our proprietary technology, DEFEND™, powered by Microban®, which continuously fights the growth of up to 99% of bacteria on the surface. Unveil the innate splendor of Calligo in its luxurious, natural state.



Cover photo features Calligo™ Almond, 15 x 30 floor tile on the wall & floor, and Tusk, 1 x 6 mosaic on the wall inset.

Above photo features Calligo™ Tusk, 15 x 30 on the floor, 12 x 24 Fluted on the middle inset and Acreage™ Palomino, 1 x 24 Mosaic on the outer insets.

STONE LOOK

USAGE



SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

CALLIGO™ + MICROBAN® PROTECTION THAT LIVES ON

GLAZED PORCELAIN FLOOR TILE AND GLAZED CERAMIC WALL AND MOSAIC TILE
with MICROBAN® TECHNOLOGY

SIZES:



15 x 30
Floor Tile



12 x 24 Fluted
Wall Tile



1 x 6
Mosaic

FINISHES: MATTE

COLOR PALETTE



TUSK



ALMOND



NIMBUS

GLAZED PORCELAIN 15 x 30 FLOOR TILE



TUSK CA41



ALMOND CA42



NIMBUS CA43

GLAZED CERAMIC 12 x 24 FLUTED WALL TILE



TUSK CA41



ALMOND CA42



NIMBUS CA43

GLAZED CERAMIC 1 x 6 MOSAIC



TUSK CA41



ALMOND CA42



NIMBUS CA43



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	15 x 30 Floor Tile	(15-3/8" x 30-1/2") (39.15 cm x 77.60 cm)	5/16"	16.35	5
	12 x 24 Fluted Wall Tile*	(11-3/4" x 23-3/4") (29.92 cm x 60.43 cm)	5/16"	15.56	8
	1 x 6 Mosaic (Dot-mounted)	(11-1/2" x 9-3/4" Sheet) (29.21 cm x 24.76 cm Sheet)	5/16"	8.30	10

* TRU-EDGE™ applies to Wall tile only.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓*
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors – Standard Center Drain (Residential or Light Commercial)	≥ 0.42	✓**
Shower Floors – Linear Drain	> 0.60	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓*
Pool Linings	N/A	✓**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior application (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Floor and Mosaic tile only.

** Mosaic tile only.

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	1 x 6 Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs	120 - 230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0 - 6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

TRIM

Type	Number	Size	Pieces/ Carton
 Floor Bullnose	P439B	3 x 15	20
 Jolly*	S1/212J	1/2 x 12	12

* Microban® Technology does not apply.

INSTALLATION

Grout Joint Recommendation	Shade Variation
----------------------------	-----------------

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)

Wall: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)



Mosaic: 1/8"

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	4 All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a white latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2024 Daltile (1/24)