

CONCRETE LOOK

CHORD™

COLORBODY™ PORCELAIN FLOOR AND MOSAIC TILE



daltile®

CHORD™

COLORBODY™ PORCELAIN FLOOR AND MOSAIC TILE

March to your own beat with the melodious collection, Chord. Find rhythm in the appeal of the 12 x 24 decorative accent which succeeds as a solo or duets beautifully with floor tile. Three colors offered in a plaster graphic and three colors offered in a cement visual with a three-inch triangle mosaic, the final note in this harmonious composition.

CONCRETE LOOK

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- REVEAL SYNC3D™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/ DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE

PC COLORBODY PORCELAIN

$ LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

IMAGINE WHAT'S POSSIBLE™ WITH DALTILE DESIGNS

Cover photo features Forte Grey 24 x 24 floor tile and 12 x 24 decorative accent in a chevron pattern on the floor.
The above photo features Forte Grey, Cement Visual, 24 x 48, with the Decorative Accent in a chevron pattern, 12 x 24, on the floor.

CONCRETE LOOK

CHORD™

COLORBODY™ PORCELAIN FLOOR AND MOSAIC TILE

SIZES:

- 24 x 48 Floor Tile
- 24 x 24 Floor Tile
- 12 x 24 Floor Tile
- 3" Triangle Mosaic Tile

FINISHES: MATTE

COLOR PALETTE


SONATA WHITE


ALLEGRO BEIGE


CANON GREY


FORTE GREY


RHYTHM BROWN


BARITONE BROWN

FLOOR TILE

PLASTER VISUAL


SONATA WHITE CH20


ALLEGRO BEIGE CH21


CANON GREY CH22

CEMENT VISUAL


FORTE GREY CH25


RHYTHM BROWN CH23


BARITONE BROWN CH24

SLIP RESISTANT

WATERPROOF

STAINPROOF

DENTPROOF

SCRATCH-RESISTANT†
†Applicable to products with Matte and Textured Finishes

FIRE-RESISTANT†
†Not Applicable to Mesh-Mounted Mosaics

CLIMATEPRO™

SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

CHORD™

COLORBODY™ PORCELAIN FLOOR AND MOSAIC TILE

CONCRETE LOOK

3" TRIANGLE MOSAIC TILE



SONATA WHITE
CH20



ALLEGRO BEIGE
CH21



CANON GREY
CH22



FORTE GREY
CH25



RHYTHM BROWN
CH23



BARITONE BROWN
CH24

DECORATIVE ACCENT PATTERN OPTIONS

(SHOWN IN ALLEGRO BEIGE)



OPTION 1: CHEVRON PATTERN



OPTION 2: DIAMOND PATTERN

CONCRETE LOOK

CHORD™

COLORBODY™ PORCELAIN FLOOR AND MOSAIC TILE

SIZES

			Thickness	Finish	Made in U.S.A.
	24 x 48 Floor Tile	23-3/8" x 46-15/16" (59.44 cm x 119.20 cm)	5/16"	M	
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	M	
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	M	
	3" Triangle Mosaic Tile (Mesh-mounted)	11-5/8" x 14-1/2" Sheet (29.53 x 36.83 cm Sheet)	5/16"	M	

Made in the U.S.A. designation is subject to change. Please visit daltile.com for the most current manufacturing information.

M Matte Finish

TRIM

	Type	Number	Size	Finish
	Floor Bullnose	P43F9	3 x 24	M
	Cove Base	P36C9	6 x 12	M
	Cove Base Outcorner	PC36C9	1 x 6	M

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position. Cove base and cove corner trim are suitable for non-freezing climates only.

M Matte Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors – Standard Center Drain	≥ 0.42	✓*
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates when proper installation methods are followed.

* Mosaic tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.) **Mosaic Tile:** 1/8"	High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	≥ 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

PRE-CONSUMER RECYCLED MATERIALS

REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

ZEROTOX

CERTIFIED PORCELAIN TILE 0.5% or less water absorption

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at **daltile.com.**

daltile®

©2026 Daltile (10/26)