



MOSAIC LOOK

FLOOR | WALL | COUNTERTOP
CITY LIGHTS™
GLASS MOSAICS



 **daltile®**
IMAGINE WHAT'S POSSIBLE™

FLOOR | WALL | COUNTERTOPS

CITY LIGHTS™

GLASS MOSAICS

Vibrancy, radiance, and pure shimmer.

Add eye-catching attention to your space and leave the room in a trance with the glow of these glass mosaics. Sixteen new stunning blends inspired by the world's most exciting cities will bring sophisticated excitement to your design. This beautiful collection offers ultimate versatility being used commercially or residentially to create borders, backsplashes, or entire walls. Let your personality shine through the City Lights Collection.

MOSAIC LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



GLASS



LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

Cover photo features Barcelona 1/2 x 1/2 mosaic with Veranda Tones in Zen Garden 6-1/2 x 20 field tile. Photo features South Beach 1/2 x 1/2 mosaic on the walls.

SIZES:



1/2 x 1/2
Mosaic Blend

FINISHES: GLOSSY

MOSAIC TILE



ST. MORITZ CL65*



SOUTH BEACH CL71*



HONOLULU CL72**



MONTE CARLO CL63**



PARIS CL67*



ST. THOMAS CL70**



RIO CL73**



BANGKOK CL61**



HOLLYWOOD CL64*



FIJI CL75*




LAS VEGAS CL69**




MANHATTAN CL74**



BARCELONA CL66**



CAPRI CL68**



TOKYO CL62*



LONDON CL60**

CITY LIGHTS™

GLASS MOSAICS

MOSAIC LOOK

SIZES

| | Thickness | Sq. Ft./ Carton | Pieces/ Carton |
|---|-----------|--|----------------|
|  1/2 x 1/2 Mosaic Blend (Mesh and/or paper face-mounted on 1' x 1' Sheet) | 1/8" | 20.74 | 22 |
| | | (11-1/2" x 11-1/2" Sheet) (29.21 cm x 29.21 cm Sheet) | |

APPLICATIONS

| | Target DCOF wet | Suitable |
|--|-----------------|----------|
| Dry & Level – Interior Floor | N/A | ✓* |
| Wet & Level – Interior Floor | ≥ 0.42 | ✓* |
| Shower Floors (Residential or Light Commercial) | ≥ 0.42 | |
| Exterior Floor Applications (including pool decking & other wet areas with minimal footwear) | ≥ 0.60 | |
| Ramps & Inclines | ≥ 0.65 | |
| Walls/Backsplashes | N/A | ✓ |
| Countertops | N/A | ✓** |
| Pool Linings | N/A | ✓ |
| Pool Tank / Submerged | N/A | ✓*** |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior walls and pool linings in freezing and non-freezing climates when proper installation methods are followed.

Paper-face and mesh-mounted installation instructions are included in carton.

* Suitable for residential and light commercial floor use (such as hotel bath) not subject to outside foot traffic.

**Residential and light commercial countertops only.

***Paper-face mounted mosaics are suitable for pool tanks and submerged applications.

INSTALLATION

| Grout Joint Recommendation | Shade Variation |
|----------------------------|---|
| 1/16" Approximately |  Random (V4) |

PERFORMANCE CHARACTERISTICS

| | ASTM# | Result |
|---------------------|-------|-----------|
| Water Absorption | C373 | < 0.01% |
| Breaking Strength | C648 | > 250 lbs |
| Scratch Hardness | MOHS | 7.0 |
| Chemical Resistance | C650 | Resistant |

For additional information on test results, visit us at: daltille.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

| | | |
|-------------------------|---|------------------------------------|
| ① Residential Bathrooms | 3 | All Residential / Light Commercial |
| 2 All Residential Areas | 4 | All Residential / Commercial |

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.