



WALL

LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC



 daltile®
IMAGINE WHAT'S POSSIBLE™

LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC

A Spectacular Spectrum

The element of color is visually represented in Color Wheel™. This vibrant collection offers a wide spectrum of colorful selections from bright and pigmented hues to neutral and earthy tones. A favorite of artists and designers, Color Wheel provides the perfect palette to inspire the imagination.

- COLOR SCHEME
 - Eight rich semi-gloss and matte accent colors
 - Plus, eight coordinating neutral tones in semi-gloss and matte finishes
- ARTISTIC INSPIRATIONS
 - Stylish shapes in unique linear size options
 - With endless design opportunities, this collection is a perfect fit for residential and commercial applications



Cover photo features Color Wheel™ Linear Matte Plum Crazy 4 x 8 on the backsplash, Natural Quartzite, Lamberti Bianco on the countertop and Emerson Wood™ Butter Pecan 8 x 48 on the floor.

Above photo features Color Wheel™ Linear Matte Sea Breeze 2 x 8 on the columns and STARE Poke™ Cloud Flecks 24 x 24 matte on the floor.



WALL

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE
- FLEXFIT™

CG
GLAZED CERAMIC

LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES:



FINISHES: MATTE | SEMI-GLOSS

SEMI-GLOSS



MATTE



ACCENT



MATTE ACCENT♦



(1), (2) and (3) indicate price groups. (1) being the least expensive.

* Subject to crazing, do not use black grout.

♦ Matte Accent colors are made-to-order.



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT



SIMPLICLEAN™







VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC

WALL










SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	8 x 24 Wall Tile	(8" x 24") (20.34 cm x 61.03 cm)	3/8" (9.30 mm)	13.30	10
	6 x 18 Wall Tile	(6" x 18") (15.25 cm x 45.76 cm)	3/8" (9.30 mm)	11.25	15
	4 x 16 Wall Tile	(4" x 16") (10.17 cm x 40.68 cm)	3/8" (9.30 mm)	13.20	30
	4 x 12 Wall Tile	(4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16" (7.90 mm)	10.64	28
	4 x 8 Wall Tile	(4-1/4" x 8-9/16") (10.91 cm x 21.82 cm)	5/16" (7.90 mm)	10.63	42
	2 x 8 Wall Tile	(2-1/8" x 8-9/16") (5.45 cm x 21.82 cm)	5/16" (7.90 mm)	10.40	80

LRV & MUNSELL

Color #	LRV Illuminate-OBS: F02-02 (CWF)	Munsell
SEMI-GLOSS		
0190	83.9	7.0Y 9.2/0.2
K175	75.9	5.2Y 8.8/0.9
0161	48.0	1.7Y 7.3/1.5
0109	37.9	6.0Y 6.6/1.0
X114	43.7	1.4GY 7.0/0.3
0182	22.6	1.9B 5.3/0.1
0180	11.4	1.3B 3.9/0.4
K111	5.0	10.0B 2.6/0.1
MATTE		
0790	83.4	4.9Y 9.2/0.2
K775	75.9	5.2Y 8.8/0.9
0761	48.1	2.5Y 7.3/1.5
0709	36.9	5.6Y 6.5/1.0
X714	43.9	3.6GY 7.0/0.4
0782	22.3	9.8G 5.3/0.1
0780	11.1	0.6B 3.9/0.4
K711	5.8	3.3PB 2.8/0.1
ACCENT		
K189	5.9	5.0PB 2.9/1.2
1012	48.1	9.7YR 7.2/6.9
1049	18.0	1.9B 5.0/4.5
1097	26.4	10.1R 5.6/10.2
0115	12.4	3.4G 4.2/4.6
1174	9.1	5.8PB 3.6/5.6
1178	6.8	5.9RP 3.1/2.0
SH17	14.0	5.1R 4.4/11.1
MATTE ACCENT		
0715	12.7	4.1G 4.3/4.4
7012	48.2	9.8YR 7.2/6.9
7049	18.2	2.0B 5.0/4.6
7097	26.8	10.0R 5.5/10.1
7174	9.3	5.8PB 3.7/5.6
7178	7.9	4.4RP 3.3/1.8
K789	6.0	5.1PB 2.9/1.2
SH77	15.1	4.7R 4.6/10.9

TRIM

		Thickness	Pieces/ Carton	
	S1/212J / 1/2 x 12 Jolly	(1/2" x 11-15/16") (1.29 cm x 30.36 cm)	1/4" (7.23 mm)	12
	S44D9 / 4 x 16 Bullnose (on 16" side)	(4" x 16") (10.17 cm x 40.68 cm)	3/8" (9.30 mm)	24
	SN44D9 / 4 x 4 Bullnose Corner	(4" x 4") (10.17 cm x 10.17 cm)	3/8" (9.30 mm)	20
	S44C9MOD / 4 x 12 Bullnose (on 12" side)	(4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16" (7.90 mm)	28
	S4489MOD / 4 x 8 Bullnose (on 8" side)	(4-1/4" x 8-9/16") (10.91 cm x 21.82 cm)	5/16" (7.90 mm)	42
	SCRL4449 / 4 x 4 Bullnose Corner	(4-1/4" x 4-1/4") (10.91 cm x 10.91 cm)	5/16" (7.90 mm)	100
	S4289MOD / 2 x 8 Bullnose (on 8" side)	(2-1/8" x 8-9/16") (5.45 cm x 21.82 cm)	5/16" (7.90 mm)	80
	SN4289M / 2 x 2 Bullnose Corner	(2-1/8" x 2-1/8") (5.45 cm x 5.45 cm)	5/16" (7.90 mm)	25
	A34C1MOD / 4 x 12 Flat Top Cove Base	(4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16" (7.90 mm)	40

TRIM USAGE

Wall Tile	8x24	6x18	4x16	4x12	4x8	2x8
Jolly	S1/212J	S1/212J	S1/212J	S1/212J	S1/212J	S1/212J
Quarter Round	A106	A106	A106	A106	A106	A106
Quarter Round Corner	AC106	AC106	AC106	AC106	AC106	AC106

SURFACE BULLNOSE

Bullnose	S44D9	S44C9MOD	S4489MOD	S4289MOD
Corner	SN44D9	SCRL4449	SCRL4449	SN4289M

RADIUS BULLNOSE

Bullnose	A4200	A4200	A4200	A4200	A4200	A4200
Corner	AN4200	AN4200	AN4200	AN4200	AN4200	AN4200

FLAT TOP COVE BASE

Cove Base	A34C1MOD	A34C1MOD	A34C1MOD	A34C1MOD	A34C1MOD	A34C1MOD
Cove Base Corner*	SCR3401 & SCL3401	SCR3401 & SCL3401	SCR3401 & SCL3401	SCR3401 & SCL3401	SCR3401 & SCL3401	SCR3401 & SCL3401

* See Color Wheel Classic product line.



APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:


Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>6 x 18 & 8 x 24: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%)</p> <p>2 x 8, 4 x 12, & 4 x 16: 1/16" (When rectangular size is installed in a staggered brick joint pattern, overlap should not exceed 33%)</p> <p>4 x 8: 1/16"</p>	 Low (V1)

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.



**POST-CONSUMER
RECYCLED MATERIALS**



**PRE-CONSUMER
RECYCLED MATERIALS**

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.

 **daltile®**

IMAGINE WHAT'S POSSIBLE™

©2023 Daltile (7/23)