



WALL

CONTEMPEE™  
GLAZED CERAMIC WALL

 daltile®



# CONTEMPEE™

GLAZED CERAMIC WALL

Delight in the artisanal elegance of Contempee, a wall tile designed with uneven edges, dimensional structures, and a crackle finish. Mix and match the handcrafted tile and star-shaped accents, which boasts high variation from piece to piece. The nature-inspired palette adds warmth and depth, perfect for feature walls, pantry nooks, and bar faces. Contempee offers a garden of choice and color to suit every design aesthetic.



Cover photo features Ivy, 4 x 4 Handcrafted on the wall.  
Above photo features Jasmine 4 x 4 Star on the wall.

## WALL

### USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



REVEAL SYNC3D™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



CGL  
GLAZED CERAMIC

LOW

HIGH

### SPECIAL FEATURES

SEE CHARTS FOR  
FULL PRODUCT  
DETAILS.



## SIZES:


4 x 4  
Handcrafted  
Wall Tile4 x 4  
Star  
Wall Tile

FINISHES: GLOSSY

## COLOR PALETTE




JASMINE




MARIGOLD



BONNET



IVY



FERN


## 4 x 4 HANDCRAFTED WALL TILE



JASMINE CE30




MARIGOLD CE31



BONNET CE32



IVY CE33




FERN CE34


## 4 x 4 STAR WALL TILE




JASMINE CE30




MARIGOLD CE31



BONNET CE32



IVY CE33



FERN CE34



Contempee features a crackle finish  
crafted with a glaze that recreates the  
timeless, weathered look of aged ceramics.



FIRE-RESISTANT



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

CONTEMPEE™

GLAZED CERAMIC WALL



SIZES

			Thickness	Finish	Made in U.S.A
	4 x 4 Handcrafted Wall Tile	4-1/4" x 4-1/4" (10.89 cm x 10.89 cm)	5/16"	G	
	4 x 4 Star Wall Tile	4-1/4" x 4-1/4" (10.89 cm x 10.89 cm)	5/16"	G	

G Glossy Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓*
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltille.com/DCOF](https://daltille.com/DCOF).

APPLICATION NOTES:

Interior Use Only.  
\*see ADDITIONAL NOTES section for full product application details.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16" (Features a lugged edge that creates an automatic 1/16" grout joint.)	Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120 - 230 lbf
Scratch Hardness	C1895	4.0 - 6.0
Chemical Resistance	C650	N/A*

For additional information on test results, visit us at: [daltille.com/information/TestResults](https://daltille.com/information/TestResults).

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Random visuals enhance the natural beauty of this product to achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

For additional information refer to “Factors to Consider” at: [daltille.com/Factors](https://daltille.com/Factors).

\*ADDITIONAL NOTES

Crackle tiles must be sealed with a penetrating sealer prior to grouting to prevent the grout from staining the wall tile. For best results, use a grout color to match the tile.

Any contact with staining agents including food should be cleaned immediately.

Not recommended for wet areas, countertops or floors.

Periodic resealing of crackle tile is required.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltille.com](https://daltille.com).



ZEROTOX

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at [daltille.com](https://daltille.com).



©2025 Daltille (08/25)