daltile®

CORE FUNDAMENTALS™

CHOICE | ADVANTAGE | PRIME | PLATINUM




CORE FUNDAMENTALS™

CHOICE

ADVANTAGE

PRIME

PLATINUM

STONE LOOK

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/ DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE
- FLEXFIT™

CG GLAZED CERAMIC

$ LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.



CORE FUNDAMENTALS™

CHOICE

THE **CHOICE TIER** HIGHLIGHTS THE BASICS WITH A VARIETY OF FLOOR TILE AND MOSAICS EXCELLENT FOR EVERYDAY USE.



CORE FUNDAMENTALS™ – CHOICE

GLAZED CERAMIC FLOOR & MOSAICS

STONE LOOK FINISHES: MATTE

FLOOR TILE



WEATHERED WHITE SQ20


BURROW BEIGE SQ21


SHADOW GREY SQ22


2 x 2 MOSAIC


WEATHERED WHITE SQ20


BURROW BEIGE SQ21


SHADOW GREY SQ22

AVAILABLE TILE SIZES



STONE LOOK FINISHES: MATTE

FLOOR TILE


IVORY AR04


CASPER AR05


FAWN AR02

AVAILABLE TILE SIZES



STONE LOOK FINISHES: MATTE

FLOOR TILE


FAIR CS22



BUFF CS20


IRON CS23


2 x 2 MOSAIC

FAIR CS22


BUFF CS20


IRON CS23

AVAILABLE TILE SIZES



STONE LOOK FINISHES: MATTE


FLOOR TILE



EVEREST WHITE CG05


TWILIGHT GREY CG07


CALM BEIGE CG08


2 x 2 MOSAIC


EVEREST WHITE CG05


TWILIGHT GREY CG07

CALM BEIGE CG08

AVAILABLE TILE SIZES



CORE FUNDAMENTALS™ – CHOICE

AVAILABLE SIZE & TRIM SHAPES

CHOICE

PLEASE REFER TO THE CHART BELOW FOR AVAILABILITY BASED ON COLOR CODE

FLOOR	SIZES		THICKNESS
	**18 x 18 Floor Tile**	17-11/16" x 17-11/16" (45.01 cm x 45.01 cm)	5/16"
	**15 x 15 Floor Tile**	14-5/8" x 14-5/8" (37.30 cm x 37.30 cm)	5/16"
	**12 x 24 Floor Tile**	11-13/16" x 23-11/16" (30.02 cm x 60.12 cm)	5/16"
	**12 x 12 Floor Tile**	11-13/16" x 11-13/16" (30.02 cm x 30.02 cm)	5/16"

MOSAICS	SIZES		THICKNESS
	**2 x 2 Mosaic Dot-mounted**	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"

FLOOR TRIM		
	**P43C9**	3 x 12 Floor Bullnose

			FLOOR					MOSAIC
			FIELD TILE				BULLNOSE	
COLOR #	COLOR NAME	PAGE #	18 x 18	15 x 15	12 x 24	12 x 12	P43C9	2 x 2
AR02	Fawn	5		●	●	●	●	
AR04	Ivory	5		●	●	●	●	
AR05	Casper	5		●	●	●	●	
CG05	Everest White	5	●		●	●	●	●
CG07	Twilight Grey	5	●		●	●	●	●
CG08	Calm Beige	5	●		●	●	●	●
CS20	Buff	5	●		●	●	●	●
CS22	Fair	5	●		●	●	●	●
CS23	Iron	5	●		●	●	●	●
SQ20	Weathered White	5	●		●	●	●	●
SQ21	Burrow Beige	5	●		●	●	●	●
SQ22	Shadow Grey	5	●		●	●	●	●

CORE FUNDAMENTALS™ – CHOICE

APPLICATION SPECIFICATIONS

CHOICE

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Mosaic tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Mosaic:** 1/8"	Medium (V2) SQ20, SQ21 & SQ22 High (V3) AR02, AR04, AR05, CG05 & CG07

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 3.0%
Breaking Strength	C648	> 250 lbf	> 250 lbf
Scratch Hardness	C1895	7.0	7.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

daltile®

©2026 Daltile (10/26)

STONE LOOK

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/ DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE
- FLEXFIT™

CG GLAZED CERAMIC

$ LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.



CORE FUNDAMENTALS™

ADVANTAGE

THE **ADVANTAGE TIER** IS RICH WITH A COMBINATION OF DIFFERENT FLOOR, WALL, AND MOSAICS TO EXCITE DESIGN, TO MIX AND MATCH OR CREATE A COHESIVE LOOK.



CORE FUNDAMENTALS™ – ADVANTAGE

GLAZED CERAMIC FLOOR, WALL & MOSAICS

STONE LOOK FINISHES: MATTE

FLOOR TILE


WASHED WHITE LS40


DISTRESSED BEIGE LS41


AGED GREY LS42

2 x 4 BRICK-JOINT MOSAIC


WASHED WHITE LS40


DISTRESSED BEIGE LS41


AGED GREY LS42

AVAILABLE TILE SIZES


18 x 18 Floor Tile


12 x 24 Floor Tile


12 x 12 Floor Tile


2 x 4 Brick-joint Mosaic

STONE LOOK FINISHES: MATTE

FLOOR TILE


PORTRAIT WHITE AQ01


MURAL TAUPE AQ02


RENOIR GREY AQ03

2 x 4 BRICK-JOINT MOSAIC


PORTRAIT WHITE AQ01


MURAL TAUPE AQ02


RENOIR GREY AQ03

AVAILABLE TILE SIZES


18 x 18 Floor Tile


12 x 24 Floor Tile


12 x 12 Floor Tile


2 x 4 Brick-joint Mosaic

CORE FUNDAMENTALS™ – ADVANTAGE

GLAZED CERAMIC FLOOR, WALL & MOSAICS

STONE LOOK FINISHES: MATTE

FLOOR TILE

ARIA WHITE EP20



PERCUSSION TAUPE EP21



TRUMPET GREY EP22

2 x 4 HERRINGBONE MOSAIC

ARIA WHITE EP20




PERCUSSION TAUPE EP21



TRUMPET GREY EP22

AVAILABLE TILE SIZES



18 x 18 Floor Tile
12 x 24 Floor Tile
12 x 12 Floor Tile
2 x 4 Herringbone Mosaic

CONCRETE LOOK FINISHES: MATTE

FLOOR TILE

WHITE CANVAS SV16



GOLDEN SAND SV17



CEMENT GREY SV18

2 x 2 MOSAIC

WHITE CANVAS SV16



GOLDEN SAND SV17



CEMENT GREY SV18

AVAILABLE TILE SIZES



18 x 18 Floor Tile
12 x 24 Floor Tile
2 x 2 Mosaic

CORE FUNDAMENTALS™ – ADVANTAGE

AVAILABLE SIZE & TRIM SHAPES

ADVANTAGE

PLEASE REFER TO THE CHART BELOW FOR AVAILABILITY BASED ON COLOR CODE

FLOOR	SIZES		THICKNESS
	**18 x 18 Floor Tile**	17-11/16" x 17-11/16" (45.01 cm x 45.01 cm)	5/16"
	**12 x 24 Floor Tile**	11-13/16" x 23-11/16" (30.02 cm x 60.12 cm)	5/16"
	**12 x 12 Floor Tile**	11-13/16" x 11-13/16" (30.02 cm x 30.02 cm)	5/16"
WALL	**SIZES**		**THICKNESS**
	**10 x 14 Wall Tile**	9-13/16" x 13-15/16" (24.99 cm x 35.40 cm)	5/16"
MOSAICS	**SIZES**		**THICKNESS**
	**2 x 4 Brick-joint Mosaic Dot-mounted**	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"
	**2 x 4 Herringbone Mosaic Dot-mounted**	14" x 12" Sheet (35.56 cm x 30.48 cm Sheet)	1/4"
	**2 x 2 Mosaic Dot-mounted**	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"

FLOOR TRIM		
	**P43C9**	3 x 12 Floor Bullnose

ADVANTAGE

			FLOOR				WALL		MOSAIC		
			FIELD TILE			BULLNOSE	FIELD TILE	BULLNOSE			
COLOR #	COLOR NAME	PAGE #	18 x 18	12 x 24	12 x 12	P43C9	10 X 14 AQ SATIN FINISH SV MATTE FINISH	S4310 SN4310	2 x 4 BRICK-JOINT	2 x 4 HERRINGBONE	2 x 2
AQ01	Portrait White	09	●	●	●	●			●		
AQ02	Mural Taupe	09	●	●	●	●			●		
AQ03	Renoir Grey	09	●	●	●	●			●		
EP20	Aria White	10	●	●	●	●				●	
EP21	Percussion Taupe	10	●	●	●	●				●	
EP22	Trumpet Grey	10	●	●	●	●				●	
LS40	Washed White	09	●	●	●	●			●		
LS41	Distressed Beige	09	●	●	●	●			●		
LS42	Aged Grey	09	●	●	●	●			●		
SV16	White Canvas	10	●	●		●	●				●
SV17	Golden Sand	10	●	●		●	●				●
SV18	Cement Grey	10	●	●		●	●				●

CORE FUNDAMENTALS™ – ADVANTAGE

APPLICATION SPECIFICATIONS

ADVANTAGE: AQ01 | AQ02 | AQ03 | EP20 | EP21 | EP22 | LS40 | LS41 | LS42 | SV16 | SV17 | SV18

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓**
Wet & Level – Interior Floor	≥ 0.42	✓**
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed. Wall tile suitable for walls/backsplashes only.

** Wall tile not suitable for application
* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Mosaic:** 1/8" **Wall:** 1/16"	 Medium (V2) SV16, SV17 & SV18  High (V3) AQ01, AQ02, AQ03, EP20, EP21, EP22, LS40, LS41 & LS42

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbf	120-230 lbf	> 250 lbf
Scratch Hardness	C1895	7.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

daltile®

©2026 Daltile (07/26)



STONE LOOK

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/ DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE
- FLEXFIT™

CG GLAZED CERAMIC

LOW — HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.



CORE FUNDAMENTALS™

PRIME

THE **PRIME TIER** PROVIDES ALL THE ESSENTIAL BENEFITS OF TILE WHILE OFFERING AN ARRAY OF DIFFERENT LOOKS AND DECORATIVE ACCENTS TO HEIGHTEN DESIGN.



CORE FUNDAMENTALS™ – PRIME

GLAZED CERAMIC FLOOR, WALL & MOSAICS

STONE LOOK FINISHES: MATTE & GLOSSY

FLOOR TILE

HEIRLOOM WHITE NS10



LINEAGE GREIGE NS11



HISTORIC GREY NS12

1 x 3 HERRINGBONE MOSAIC



HEIRLOOM WHITE NS10



LINEAGE GREIGE NS11



HISTORIC GREY NS12

AVAILABLE TILE SIZES




18 x 18 Floor Tile | 12 x 24 Floor Tile | 8 x 24 Wall Tile | 1 x 3 Herringbone Mosaic

STONE LOOK FINISHES: MATTE

FLOOR TILE




WHITE BALANS BA30



CHARCOAL BA34

2 x 4 MOSAIC

WHITE BALANS BA30



CHARCOAL BA34

AVAILABLE TILE SIZES



18 x 18 Floor Tile | 12 x 24 Floor Tile | 12 x 12 Floor Tile | 10 x 14 Wall Tile* | 2 x 4 Straight-joint Mosaic

*Only available in BA30.

MONOCHROMATIC LOOK FINISHES: MATTE

FLOOR TILE

RAINIER 1500



BLACK 2011

AVAILABLE TILE SIZES



12 x 12 Floor Tile

CORE FUNDAMENTALS™ – PRIME

GLAZED CERAMIC FLOOR, WALL & MOSAICS

STONE LOOK FINISHES: MATTE

FLOOR TILE


WHITE ELECT EL30


BEIGE ELECT EL31


GREY ELECT EL32

1 x 3 HERRINGBONE MOSAIC


WHITE ELECT EL30


BEIGE ELECT EL31


GREY ELECT EL32

AVAILABLE TILE SIZES



12 x 24
Floor Tile


4 x 12
Wall Tile


1 x 3
Herringbone Mosaic

CONCRETE LOOK FINISHES: MATTE


FLOOR TILE


WHITE KONCRETE KC01


GREY KONCRETE KC04

2 x 2 MOSAIC


WHITE KONCRETE KC01


GREY KONCRETE KC04

AVAILABLE TILE SIZES


18 x 18
Floor Tile


12 x 24
Floor Tile


12 x 12
Floor Tile


2 x 2
Mosaic

STONE LOOK FINISHES: MATTE


FLOOR TILE



VITALITY WHITE RL20



DYNAMIC BEIGE RL21


STAMINA GREY RL23

1.5" HEX MOSAIC


VITALITY WHITE RL20


DYNAMIC BEIGE RL21


STAMINA GREY RL23

AVAILABLE TILE SIZES


12 x 24
Floor Tile


12 x 12
Floor Tile


1.5" Hex
Mosaic

CORE FUNDAMENTALS™ – PRIME

AVAILABLE SIZE & TRIM SHAPES

PRIME

PLEASE REFER TO THE CHART BELOW FOR AVAILABILITY BASED ON COLOR CODE

FLOOR	SIZES		THICKNESS
	**18 x 18 Floor Tile**	17-11/16" x 17-11/16" (45.01 cm x 45.01 cm)	5/16"
	**12 x 24 Floor Tile**	11-13/16" x 23-11/16" (30.02 cm x 60.12 cm)	5/16"
	**12 x 12 Floor Tile**	11-13/16" x 11-13/16" (30.02 cm x 30.02 cm)	5/16"

WALL	SIZES		THICKNESS
	**8 x 24 Wall Tile**	8" x 24" (20.34 cm x 61.30 cm)	3/8"
	**10 x 14 Wall Tile**	9-13/16" x 13-15/16" (24.99 cm x 35.43 cm)	5/16"
	**4 x 12 Wall Tile**	4-1/4" x 12-7/8" (10.88 cm x 32.76 cm)	5/16"

MOSAICS	SIZES		THICKNESS
	**2 x 4 Straight-joint Mosaic Dot-mounted**	12" x 12" Sheet (30.48 x 30.48 cm Sheet)	1/4"
	**2 x 2 Mosaic Dot-mounted**	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"
	**1.5" Hex Mosaic Dot-mounted**	11-3/8 "x 10-1/4" Sheet (28.89 cm x 26.04 cm Sheet)	1/4"
	**1 x 3 Herringbone Mosaic Dot-mounted**	9" x 12" Sheet (22.86 x 30.48 cm Sheet)	1/4"

FLOOR TRIM		
	**P43F9**	3 x 24 Floor Bullnose
	**P43C9**	3 x 12 Floor Bullnose

WALL TRIM		
	S1/212J	12" Jolly
	**S4310**	3 x 10 Wall Bullnose
	**SN4310**	3 x 3 Wall Bullnose Corner

			FLOOR					WALL					MOSAIC			
			FIELD TILE			BULLNOSE		FIELD TILE			BULLNOSE					
COLOR #	COLOR NAME	PAGE #	18 x 18	12 x 24	12 x 12	P43F9	P43C9	10 x 14 Matte	8 x 24 Glossy	4 x 12 Matte	S4310 SN4310	S1/212J	2 x 4 STRAIGHT-JOINT	2 x 2	1.5 HEXAGON	1 x 3 HERRINGBONE
BA30	White Balans	15	●	●	●		●	●			●		●			
BA34	Charcoal	15	●	●	●		●						●			
EL30	White Elect	16		●		●				●		●				●
EL31	Beige Elect	16		●		●				●		●				●
EL32	Grey Elect	16		●		●				●		●				●
KC01	White Koncrete	16	●	●	●		●							●		
KC04	Grey Koncrete	16	●	●	●		●							●		
NS10	Heirloom White	15	●	●			●		●			●				●
NS11	Lineage Greige	15	●	●			●		●			●				●
NS12	Historic Grey	15	●	●			●		●			●				●
RL20	Vitality White	16		●	●	●									●	
RL21	Dynamic Beige	16		●	●	●									●	
RL23	Stamina Grey	16		●	●	●									●	
1500	Rainier	15			●		●									
2011	Black	15			●		●									

CORE FUNDAMENTALS™ – PRIME

APPLICATION SPECIFICATIONS

PRIME: BA30 | BA34 | KC01 | KC04 | NS10 | NS11 | NS12

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓**
Wet & Level – Interior Floor	≥ 0.42	✓**
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

** Wall tile not suitable for this application

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Wall:** 1/16" **Mosaic:** 1/8"	Medium (V2) NS10, NS11 & NS12 High (V3) BA30, BA34, KC01 & KC04

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbf	120-230 lbf	> 250 lbf
Scratch Hardness	C1895	7.0	4.0-6.0	7.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

PRIME: EL30 | EL31 | EL32

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓**
Wet & Level – Interior Floor	≥ 0.42	✓**
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

** Wall tile not suitable for this application

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Wall:** 1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%) **Mosaic:** 1/8"	High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbf	120-230 lbf	> 250 lbf
Scratch Hardness	C1895	8.0	4.0-6.0	7.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

CORE FUNDAMENTALS™ – PRIME

APPLICATION SPECIFICATIONS

PRIME: RL20 | RL21 | RL23

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Mosaic:** 1/8"	High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 3.0%
Breaking Strength	C648	> 250 lbf	> 250 lbf
Scratch Hardness	C1895	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

PRIME: 1500 | 2011

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	
Shower Floor – Standard Center Drain	≥ 0.42	
Shower Floor – Linear Drain	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 7.0%
Breaking Strength	C648	> 250 lbf
Scratch Hardness	C1895	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

daltile®

©2026 Daltile (10/26)



STONE LOOK

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/ DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE
- FLEXFIT™

PG GLAZED PORCELAIN | CG GLAZED CERAMIC

LOW — HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

CORE FUNDAMENTALS™

PLATINUM

THE **PLATINUM TIER** OFFERS THE LOOK OF LUXURY, COMBINING MARBLE, WOOD, AND STONE LOOKS FOR A SOPHISTICATED SELECTION THAT OFFERS ENDLESS DESIGN POSSIBILITIES AND EXCEPTIONAL VERSATILITY.



CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

STONE LOOK FINISHES: MATTE

FLOOR TILE



WHITE AVERY AV17



BEIGE AVERY AV18



GREY AVERY AV19

AVAILABLE TILE SIZES



12 x 24
Floor Tile

STONE LOOK FINISHES: MATTE

FLOOR TILE



ALABASTER SL75



JUTE SL76



QUILL SL77

2 x 2 MOSAIC



ALABASTER SL75



JUTE SL76



QUILL SL77

AVAILABLE TILE SIZES



12 x 24
Floor Tile



2 x 2
Mosaic

STONE LOOK FINISHES: MATTE

FLOOR TILE

CHALK IT50



CLIFF IT51



SHALE IT52

AVAILABLE TILE SIZES



15 x 30
Floor Tile




2 x 2
Mosaic

2 x 2 MOSAIC



CHALK IT50



CLIFF IT51



SHALE IT52

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

MARBLE LOOK FINISHES: MATTE & GLOSSY

FLOOR TILE




MAGNOLIA CT70



ALMOND CT71



DOVE CT72



CARBON CT73



OYSTER CT74*



CALACATTA SKY CT75**



CALACATTA EMPIRE CT76

*CT74 available in 12 x 24, 6 x 18, 2 x 2 mosaic only.
**CT75 available in 12x24, 6x18, 4x12, and 2x2 mosaic only.


2 x 2 MOSAIC




MAGNOLIA
CT70



ALMOND
CT71



DOVE
CT72




CARBON
CT73



OYSTER
CT74



CALACATTA SKY
CT75



CALACATTA EMPIRE
CT76


1 x 4 MOSAIC



MAGNOLIA
CT70



ALMOND
CT71



DOVE
CT72



CARBON
CT73

OYSTER
CT74

AVAILABLE TILE SIZES



24 x 24
Floor Tile



12 x 24
Floor Tile



12 x 12
Floor Tile



6 x 18
Wall Tile**

4 x 12
Wall Tile



2 x 2 Straight-joint
Mosaic



1 x 4 Herringbone
Mosaic***

* Not available in CT73.
** Available in CT75 & CT76 only.
*** Excluding CT75 or CT76.

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

MARBLE LOOK FINISHES: MATTE & GLOSSY

FLOOR TILE


CLOUD PH60



MIST PH61



SAND PH62




SMOKE PH63


2 x 2 MOSAIC




CLOUD PH60



MIST PH61



SAND PH62



SMOKE PH63

AVAILABLE TILE SIZES



15 x 30
Floor Tile



12 x 24
Wall Tile*



2 x 2
Mosaic

*PH60, PH61 & PH62 only.

WOOD LOOK FINISHES: MATTE

FLOOR TILE



NATURAL HILL HOUSE HH01



GREIGE HH02




TEAK HH03



DARK BROWN HILL HOUSE HH04

AVAILABLE TILE SIZES



6 x 36
Floor Tile

WOOD LOOK FINISHES: MATTE

FLOOR TILE



NATURAL RESEMBLANCE RB10



BROWN RESEMBLANCE RB11



MEDIUM GRAY RB12



LIGHT GRAY RB13

AVAILABLE TILE SIZES



6 x 24
Floor Tile

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

WOOD LOOK FINISHES: MATTE

FLOOR TILE



WHITE BROXBURN VL50



BROWN BROXBURN VL51



DARK BROWN BROXBURN VL52



GRAY VL53

AVAILABLE TILE SIZES

6 x 24
Floor Tile

WOOD LOOK FINISHES: MATTE

FLOOR TILE



WHITE VICINITY VC01



NATURAL VICINITY VC02



HONEY VC03



BROWN VICINITY VC04



GRAY BROWN VC05

AVAILABLE TILE SIZES

6 x 36
Floor Tile

WOOD LOOK FINISHES: MATTE

FLOOR TILE



LOFT TH10



AVENUE TH11



VINTAGE TH12



CAVALRY TH13

AVAILABLE TILE SIZES

8 x 48
Floor Tile

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

CONCRETE LOOK FINISHES: MATTE

FLOOR TILE




WHITE URBANIZE UB02



GREY URBANIZE UB04

2 x 2 MOSAIC

WHITE URBANIZE UB02



GREY URBANIZE UB04

AVAILABLE TILE SIZES



12 x 24
Floor Tile






2 x 2 Straight-joint
Mosaic

CORE FUNDAMENTALS™ – PLATINUM

AVAILABLE SIZE & TRIM SHAPES

PLATINUM

PLEASE REFER TO CHART ON NEXT PAGE FOR AVAILABILITY BASED ON COLOR CODE

FLOOR	SIZES		THICKNESS
	**15 x 30 Floor Tile**	15-3/8" x 30-1/2" (39.15 cm x 77.60 cm)	5/16"
	**24 x 24 Floor Tile**	23-13/16" x 23-13/16" (60.48 cm x 60.48 cm)	5/16"
	**12 x 24 Floor Tile**	11-7/8" x 23-5/8" (30.23 cm x 60.12 cm)	5/16"
	**12 x 12 Floor Tile**	11-13/16" x 11-13/16" (30.00 cm x 30.00 cm)	5/16"
	**8 x 48 Floor Tile**	7-15/16" x 47-3/16" (20.26 cm x 120.00 cm)	3/8"
	**6 x 36 Floor Tile**	5-15/16" x 35-7/16" (15.19 cm x 90.00)	5/16"
	**6 x 24 Floor Tile**	6-1/16" x 23-7/8" (15.43 cm x 60.60 cm)	5/16"
WALL	**SIZES**		**THICKNESS**
	4 x 12 Wall Tile	4-1/4" x 12-7/8" (10.91 cm x 32.77 cm)	5/16"
	**6 x 18 Wall Tile**	6" x 18" (15.25 cm x 45.77 cm)	5/16"
	**12 x 24 Wall Tile**	12" x 24" (30.51 cm x 61.03 cm)	3/8"

MOSAICS	SIZES		THICKNESS
	**2 x 2 Mosaic Dot-mounted**	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"
	**1 x 4 Herringbone Mosaic**	12" x 11-3/4" Sheet (30.48 cm x 26.035 cm Sheet)	1/4"

FLOOR TRIM		
	**P43C9**	3 x 12 Floor Bullnose
	**P439B**	3 x 15 Floor Bullnose
	**P43F9**	3 x 24 Floor Bullnose
WALL TRIM		
	S1/212J	12" Jolly

CORE FUNDAMENTALS™ – PLATINUM

AVAILABLE SIZE & TRIM SHAPES

PLATINUM

			FLOOR										WALL				MOSAIC	
			FIELD TILE							BULLNOSE			FIELD TILE			JOLLY		
COLOR #	COLOR NAME	PAGE #	15 x 30	24 x 24	12 x 24	12 x 12	8 x 48	6 x 36	6 x 24	P439B	P43C9	P43F9	12 x 24 Glossy	6 x 18 Glossy	4 x 12 Matte	S1/212J	2 x 2	1 x 4 Herringbone
AV17	White Avery	21			●						●							
AV18	Beige Avery	21			●						●							
AV19	Grey Avery	21			●						●							
CT70	Magnolia	22		●	●	●					●						●	●
CT71	Almond	22		●	●	●					●						●	●
CT72	Dove	22		●	●	●					●						●	●
CT73	Carbon	22		●	●	●					●						●	●
CT74	Oyster	22			●						●						●	●
CT75	Calacatta Sky	22			●						●			●		●	●	
CT76	Calacatta Empire	22		●	●	●					●			●	●	●	●	
HH01	Natural Hill House	23						●										
HH02	Greige	23						●										
HH03	Teak	23						●										
HH04	Dark Brown Hill House	23						●										
IT50	Chalk	21	●							●							●	
IT51	Cliff	21	●							●							●	
IT52	Shale	21	●							●							●	
PH60	Cloud	23	●							●			●			●	●	
PH61	Mist	23	●							●			●			●	●	
PH62	Sand	23	●							●			●			●	●	
PH63	Smoke	23	●							●							●	
RB10	Natural Resemblence	23							●									
RB11	Brown Resemblence	23							●									
RB12	Medium Gray	23							●									
RB13	Light Gray	23							●									
SL75	Alabaster	21			●							●					●	
SL76	Jute	21			●							●					●	
SL77	Quill	21			●							●					●	
TH10	Loft	24					●											
TH11	Avenue	24					●											
TH12	Vintage	24					●											
TH13	Cavalry	24					●											
UB02	White Urbanize	25			●						●						●	
UB04	Grey Urbanize	25			●						●						●	
VL50	White Broxburn	24							●									
VL51	Brown Broxburn	24							●									
VL52	Dark Brown Broxburn	24							●									
VL53	Gray	24							●									
VC01	White Vicinity	24						●										
VC02	Natural Vicinity	24						●										
VC03	Honey	24						●										
VC04	Brown Vicinity	24						●										
VC05	Gray Brown	24						●										

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

PLATINUM: AV17, AV18, AV19 | HH01, HH02, HH03, HH04 | RB10, RB11, RB12, RB13 | TH10, TH11, TH12, TH13 | VL50, VL51, VL52, VL53 | VC01, VC02, VC03, VC04, VC05

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floor – Standard Center Drain	≥ 0.42	
Shower Floor – Linear Drain	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

PLATINUM: CT70, CT71, CT72, CT73, CT74, CT75, CT76 | PH60, PH61, PH62, PH63 | UB02, UB04 | | SL75, SL76, SL77 | IT50, IT51, IT52 |

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓**
Wet & Level – Interior Floor	≥ 0.42	✓**
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Floor tile and 1x4 mosaic suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic and Wall tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

** Wall tile not suitable for this application

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Wall**: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%. Excluding 4 x 12 option.) **Mosaic:** 1/8"	Medium (V2) PH60, PH61, PH62 & PH63 High (V3) CT70, CT71, CT72, CT73, CT74, CT75, CT76, UB02 & UB04, IT50, IT51, IT52, SL75, SL76 & SL77

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbf	120-230 lbf	> 250 lbf
Scratch Hardness	C1895	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

daltile®

©2026 Daltile (10/26)

IMAGE DIRECTORY

COVER
Photo features Core Fundamentals™ Platinum Brown VC04 on the floor with One Quartz Surfaces® Freedom Calacatta OQ42 on the countertop.

PAGE 2
Photo features Core Fundamentals™ Prime White Balans BA30 on the floor.

PAGE 3 – CHOICE
Photo features Core Fundamentals™ Choice Iron CS23 on the floor.

PAGE 3 – ADVANTAGE
Photo features Core Fundamentals™ Advantage Trumpet Grey EP22 on the floor with Aria White EP20 on the wall and Natural Stone Quartzite Slab Lamberti Bianco QO15 on the countertop.

PAGE 3 – PRIME
Photo features Core Fundamentals™ Prime Grey EL32 on the floor with Revalia™ Remix Radiant Blue RV33 on the wall.

PAGE 3 – PLATINUM
Photo features Core Fundamentals™ Platinum Mist PH61 on the floor and shower floor with Artcrafted™ Coconut AC23 on the shower walls and Panoramic Porcelain Surfaces™ Calacatta Aries CM21 on the countertop.

PAGE 4
Photo features Core Fundamentals™ Weathered White SQ20 on the floor with Shadow Grey SQ22 on the backsplash.

PAGE 8
Photo features Core Fundamentals™ Advantage Distressed Beige LS41 on the floor and shower floor with Mesmerist™ Allure MM33 on the shower walls and Natural Stone Slab Granite Colonial Gold G422 on the countertop and shower bench.

PAGE 13
Photo features Core Fundamentals™ Advantage Mural Taupe AQ02 on the floor with One Quartz Surfaces® Patriotic OQ47 on the countertop.

PAGE 14
Photo features Core Fundamentals™ Prime Historic Grey NS12 on the floor with Heirloom White NS10 on the wall and Natural Stone Granite Slab White River G848 on the countertop.

PAGE 22
Photo features Core Fundamentals™ Platinum Smoke PH63 on the floor with One Quartz Surfaces® Pulsar OQ61 on the countertop.

PAGE 25
Photo features Core Fundamentals™ Platinum Brown VC04 on the floor with One Quartz Surfaces® Freedom Calacatta OQ42 on the countertop.

BACK COVER
Photo features Core Fundamentals™ Platinum Calacatta Empire CT76 on the floor, shower floor and shower walls with Natural Stone Granite Slab Himalaya White G217 on the countertop.


IMAGINE WHAT'S POSSIBLE™
WITH DALTILE DESIGNS