

STONE
LOOK

USAGE



COUNTERTOP

SHOWER
FLOOR

EXTERIOR
FLOOR

STEPWISE™

TRU-EDGE™

MADE IN
THE U.S.A.

LARGE
FORMAT

MOSAIC/
DECO

ENCAUSTIC

TERRAZZO

PAVER

CUSTOMIZE

FLEXFIT™

LOW HIGH

SPECIAL FEATURES



CORE FUNDAMENTALS™ PLATINUM

THE **PLATINUM TIER** OFFERS THE LOOK OF LUXURY, COMBINING MARBLE, WOOD, AND STONE LOOKS FOR A SOPHISTICATED SELECTION THAT OFFERS ENDLESS DESIGN POSSIBILITIES AND EXCEPTIONAL VERSATILITY.



NOT APPLICABLE
FOR ALL PRODUCTS
IN THIS SERIES. SEE CHARTS
FOR FULL PRODUCT DETAILS.

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

STONE LOOK FINISHES: MATTE

FLOOR TILE



WHITE AV17



BEIGE AV18



GREY AV19

AVAILABLE TILE SIZES



12 x 24
Floor Tile

MARBLE LOOK FINISHES: MATTE

FLOOR TILE



CALACATTA SKY CT75




CALACATTA EMPIRE CT76

2 x 2 MOSAIC



CALACATTA SKY
CT75



CALACATTA EMPIRE
CT76

AVAILABLE TILE SIZES



12 x 24
Floor Tile



12 x 12
Floor Tile



4 x 12
Wall Tile



2 x 2
Mosaic

WOOD LOOK FINISHES: MATTE

FLOOR TILE



NATURAL HH01



GREIGE HH02



TEAK HH03



DARK BROWN HH04

AVAILABLE TILE SIZES



6 x 36
Floor Tile

WOOD LOOK FINISHES: MATTE

FLOOR TILE



NATURAL RB10



BROWN RB11



MEDIUM GRAY RB12



LIGHT GRAY RB13

AVAILABLE TILE SIZES



6 x 24
Floor Tile

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR, WALL & MOSAICS

WOOD LOOK FINISHES: MATTE

FLOOR TILE




WHITE VL50



BROWN VL51



DARK BROWN VL52



GRAY VL53

AVAILABLE TILE SIZES



6 x 24
Floor Tile

WOOD LOOK FINISHES: MATTE

FLOOR TILE



WHITE VC01



NATURAL VC02



HONEY VC03



BROWN VC04



GRAY BROWN VC05

AVAILABLE TILE SIZES



6 x 36
Floor Tile

CONCRETE LOOK FINISHES: MATTE

FLOOR TILE




WHITE UB02




GREY UB04

2 x 2 MOSAIC



WHITE UB02



GREY UB04

AVAILABLE TILE SIZES



12 x 24
Floor Tile



2 x 2
Mosaic

MARBLE LOOK FINISHES: MATTE & GLOSSY

FLOOR TILE




CLOUD PH60



MIST PH61



SAND PH62



SMOKE PH63

2 x 2 MOSAIC




CLOUD PH60



MIST PH61



SAND PH62



SMOKE PH63

AVAILABLE TILE SIZES



15 x 30
Floor Tile
Matte



12 x 24
Wall Tile
Glossy














2 x 2
Mosaic
Matte

CORE FUNDAMENTALS™ – PLATINUM

AVAILABLE SIZE & TRIM SHAPES

PLATINUM

PLEASE REFER TO CHART ON NEXT PAGE FOR AVAILABILITY BASED ON COLOR CODE

FLOOR	SIZES	THICKNESS	MOSAICS	SIZES	THICKNESS
	15 x 30 Floor Tile (15-3/8" x 30-1/2") (39.15 cm x 77.60 cm)	5/16"		2 x 2 Mosaic Dot-mounted (12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"
	12 x 24 Floor Tile (11-7/8" x 23-5/8") (30.23 cm x 60.12 cm)	5/16"	FLOOR TRIM		
	12 x 12 Floor Tile (11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"		P43C9	3 x 12 Floor Bullnose
	6 x 36 Floor Tile (5-15/16" x 35-7/16") (15.19 cm x 90.00)	5/16"		P43B9	3 x 15 Floor Bullnose
	6 x 24 Floor Tile (6-1/16" x 23-7/8") (15.43 cm x 60.60 cm)	5/16"	WALL TRIM		
	4 x 12 Wall Tile (4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16"		S1/212J	12" Jolly
	12 x 24 Wall Tile (12" x 24") (30.51 cm x 61.03 cm)	3/8"			

COLOR #	COLOR NAME	PAGE #	FLOOR						WALL				MOSAIC
			FIELD TILE					BULLNOSE		FIELD TILE		JOLLY	
			15 x 30	12 x 24	12 x 12	6 x 36	6 x 24	P43B9	P43C9	12 x 24 Glossy	4 x 12 Matte	S1/212J	
AV17	White	21		●					●				
AV18	Beige	21		●					●				
AV19	Grey	21		●					●				
CT75	Calacatta Sky	21		●					●	●	●	●	
CT76	Calacatta Empire	21		●	●				●	●	●	●	
HH01	Natural	21				●							
HH02	Greige	21				●							
HH03	Teak	21				●							
HH04	Dark Brown	21				●							
RB10	Natural	21					●						
RB11	Brown	21					●						
RB12	Medium Gray	21					●						
RB13	Light Gray	21					●						
UB02	White	22		●					●				●
UB04	Grey	22		●					●				●
VL50	White	22						●					
VL51	Brown	22						●					
VL52	Dark Brown	22						●					
VL53	Gray	22						●					
VC01	White	22				●							
VC02	Natural	22				●							
VC03	Honey	22				●							
VC04	Brown	22				●							
VC05	Gray Brown	22				●							
PH60	Cloud	22	●						●	●	●	●	●
PH61	Mist	22	●						●	●	●	●	●
PH62	Sand	22	●						●	●	●	●	●
PH63	Smoke	22	●						●	●	●	●	●

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR, WALL & MOSAICS

PLATINUM: AV17, AV18, AV19 | HH01, HH02, HH03, HH04 | RB10, RB11, RB12, RB13 | VL50, VL51, VL52, VL53 | VC01, VC02, VC03, VC04, VC05

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floor – Standard Center Drain	≥ 0.42	
Shower Floor – Linear Drain	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation **Shade Variation**

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

PLATINUM: CT75, CT76 | PH60, PH61, PH62, PH63 | UB02, UB04

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓**
Wet & Level – Interior Floor	≥ 0.42	✓**
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

** Wall tile not suitable for this application

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation **Shade Variation**

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



Wall: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)



Mosaic: 1/8"

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial