

STONE LOOK

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/ DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE
- FLEXFIT™

PG GLAZED PORCELAIN | CG GLAZED CERAMIC

LOW — HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

CORE FUNDAMENTALS™

PLATINUM

THE **PLATINUM TIER** OFFERS THE LOOK OF LUXURY, COMBINING MARBLE, WOOD, AND STONE LOOKS FOR A SOPHISTICATED SELECTION THAT OFFERS ENDLESS DESIGN POSSIBILITIES AND EXCEPTIONAL VERSATILITY.



CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

STONE LOOK FINISHES: MATTE

FLOOR TILE



WHITE AVERY AV17



BEIGE AVERY AV18



GREY AVERY AV19

AVAILABLE TILE SIZES



12 x 24
Floor Tile

STONE LOOK FINISHES: MATTE

FLOOR TILE



ALABASTER SL75



JUTE SL76



QUILL SL77

2 x 2 MOSAIC



ALABASTER SL75



JUTE SL76



QUILL SL77

AVAILABLE TILE SIZES



12 x 24
Floor Tile



2 x 2
Mosaic

STONE LOOK FINISHES: MATTE

FLOOR TILE

CHALK IT50



CLIFF IT51



SHALE IT52

AVAILABLE TILE SIZES



15 x 30
Floor Tile




2 x 2
Mosaic

2 x 2 MOSAIC



CHALK IT50



CLIFF IT51



SHALE IT52

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

MARBLE LOOK FINISHES: MATTE & GLOSSY

FLOOR TILE




MAGNOLIA CT70



ALMOND CT71



DOVE CT72



CARBON CT73



OYSTER CT74*



CALACATTA SKY CT75**



CALACATTA EMPIRE CT76

*CT74 available in 12 x 24, 6 x 18, 2 x 2 mosaic only.
**CT75 available in 12x24, 6x18, 4x12, and 2x2 mosaic only.


2 x 2 MOSAIC




MAGNOLIA
CT70



ALMOND
CT71



DOVE
CT72




CARBON
CT73



OYSTER
CT74



CALACATTA SKY
CT75



CALACATTA EMPIRE
CT76


1 x 4 MOSAIC



MAGNOLIA
CT70



ALMOND
CT71



DOVE
CT72



CARBON
CT73

OYSTER
CT74

AVAILABLE TILE SIZES



24 x 24
Floor Tile



12 x 24
Floor Tile



12 x 12
Floor Tile



6 x 18
Wall Tile**

4 x 12
Wall Tile



2 x 2 Straight-joint
Mosaic



1 x 4 Herringbone
Mosaic***

* Not available in CT73.
** Available in CT75 & CT76 only.
*** Excluding CT75 or CT76.

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

MARBLE LOOK FINISHES: MATTE & GLOSSY

FLOOR TILE


CLOUD PH60



MIST PH61



SAND PH62




SMOKE PH63


2 x 2 MOSAIC




CLOUD PH60



MIST PH61



SAND PH62



SMOKE PH63

AVAILABLE TILE SIZES



15 x 30
Floor Tile



12 x 24
Wall Tile*



2 x 2
Mosaic

*PH60, PH61 & PH62 only.

WOOD LOOK FINISHES: MATTE

FLOOR TILE



NATURAL HILL HOUSE HH01



GREIGE HH02




TEAK HH03



DARK BROWN HILL HOUSE HH04

AVAILABLE TILE SIZES



6 x 36
Floor Tile

WOOD LOOK FINISHES: MATTE

FLOOR TILE



NATURAL RESEMBLANCE RB10



BROWN RESEMBLANCE RB11



MEDIUM GRAY RB12



LIGHT GRAY RB13

AVAILABLE TILE SIZES



6 x 24
Floor Tile

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

WOOD LOOK FINISHES: MATTE

FLOOR TILE



WHITE BROXBURN VL50



BROWN BROXBURN VL51



DARK BROWN BROXBURN VL52



GRAY VL53

AVAILABLE TILE SIZES

6 x 24
Floor Tile

WOOD LOOK FINISHES: MATTE

FLOOR TILE



WHITE VICINITY VC01



NATURAL VICINITY VC02



HONEY VC03



BROWN VICINITY VC04



GRAY BROWN VC05

AVAILABLE TILE SIZES

6 x 36
Floor Tile

WOOD LOOK FINISHES: MATTE

FLOOR TILE



LOFT TH10



AVENUE TH11



VINTAGE TH12



CAVALRY TH13

AVAILABLE TILE SIZES

8 x 48
Floor Tile

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

CONCRETE LOOK FINISHES: MATTE

FLOOR TILE




WHITE URBANIZE UB02



GREY URBANIZE UB04

2 x 2 MOSAIC

WHITE URBANIZE UB02



GREY URBANIZE UB04

AVAILABLE TILE SIZES



12 x 24
Floor Tile






2 x 2 Straight-joint
Mosaic

CORE FUNDAMENTALS™ – PLATINUM

AVAILABLE SIZE & TRIM SHAPES

PLATINUM

PLEASE REFER TO CHART ON NEXT PAGE FOR AVAILABILITY BASED ON COLOR CODE

FLOOR	SIZES		THICKNESS
	**15 x 30 Floor Tile**	15-3/8" x 30-1/2" (39.15 cm x 77.60 cm)	5/16"
	**24 x 24 Floor Tile**	23-13/16" x 23-13/16" (60.48 cm x 60.48 cm)	5/16"
	**12 x 24 Floor Tile**	11-7/8" x 23-5/8" (30.23 cm x 60.12 cm)	5/16"
	**12 x 12 Floor Tile**	11-13/16" x 11-13/16" (30.00 cm x 30.00 cm)	5/16"
	**8 x 48 Floor Tile**	7-15/16" x 47-3/16" (20.26 cm x 120.00 cm)	3/8"
	**6 x 36 Floor Tile**	5-15/16" x 35-7/16" (15.19 cm x 90.00)	5/16"
	**6 x 24 Floor Tile**	6-1/16" x 23-7/8" (15.43 cm x 60.60 cm)	5/16"
WALL	**SIZES**		**THICKNESS**
	4 x 12 Wall Tile	4-1/4" x 12-7/8" (10.91 cm x 32.77 cm)	5/16"
	**6 x 18 Wall Tile**	6" x 18" (15.25 cm x 45.77 cm)	5/16"
	**12 x 24 Wall Tile**	12" x 24" (30.51 cm x 61.03 cm)	3/8"

MOSAICS	SIZES		THICKNESS
	**2 x 2 Mosaic Dot-mounted**	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"
	**1 x 4 Herringbone Mosaic**	12" x 11-3/4" Sheet (30.48 cm x 26.035 cm Sheet)	1/4"

FLOOR TRIM		
	**P43C9**	3 x 12 Floor Bullnose
	**P439B**	3 x 15 Floor Bullnose
	**P43F9**	3 x 24 Floor Bullnose
WALL TRIM		
	S1/212J	12" Jolly

CORE FUNDAMENTALS™ – PLATINUM

AVAILABLE SIZE & TRIM SHAPES

PLATINUM

			FLOOR										WALL				MOSAIC	
			FIELD TILE							BULLNOSE			FIELD TILE			JOLLY		
COLOR #	COLOR NAME	PAGE #	15 x 30	24 x 24	12 x 24	12 x 12	8 x 48	6 x 36	6 x 24	P439B	P43C9	P43F9	12 x 24 Glossy	6 x 18 Glossy	4 x 12 Matte	S1/212J	2 x 2	1 x 4 Herringbone
AV17	White Avery	21			●						●							
AV18	Beige Avery	21			●						●							
AV19	Grey Avery	21			●						●							
CT70	Magnolia	22		●	●	●					●						●	●
CT71	Almond	22		●	●	●					●						●	●
CT72	Dove	22		●	●	●					●						●	●
CT73	Carbon	22		●	●	●					●						●	●
CT74	Oyster	22			●						●						●	●
CT75	Calacatta Sky	22			●						●			●		●	●	
CT76	Calacatta Empire	22		●	●	●					●			●	●	●	●	
HH01	Natural Hill House	23						●										
HH02	Greige	23						●										
HH03	Teak	23						●										
HH04	Dark Brown Hill House	23						●										
IT50	Chalk	21	●							●							●	
IT51	Cliff	21	●							●							●	
IT52	Shale	21	●							●							●	
PH60	Cloud	23	●							●			●			●	●	
PH61	Mist	23	●							●			●			●	●	
PH62	Sand	23	●							●			●			●	●	
PH63	Smoke	23	●							●							●	
RB10	Natural Resemblence	23							●									
RB11	Brown Resemblence	23							●									
RB12	Medium Gray	23							●									
RB13	Light Gray	23							●									
SL75	Alabaster	21			●							●					●	
SL76	Jute	21			●							●					●	
SL77	Quill	21			●							●					●	
TH10	Loft	24					●											
TH11	Avenue	24					●											
TH12	Vintage	24					●											
TH13	Cavalry	24					●											
UB02	White Urbanize	25			●						●						●	
UB04	Grey Urbanize	25			●						●						●	
VL50	White Broxburn	24							●									
VL51	Brown Broxburn	24							●									
VL52	Dark Brown Broxburn	24							●									
VL53	Gray	24							●									
VC01	White Vicinity	24						●										
VC02	Natural Vicinity	24						●										
VC03	Honey	24						●										
VC04	Brown Vicinity	24						●										
VC05	Gray Brown	24						●										

CORE FUNDAMENTALS™ – PLATINUM

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAICS

PLATINUM: AV17, AV18, AV19 | HH01, HH02, HH03, HH04 | RB10, RB11, RB12, RB13 | TH10, TH11, TH12, TH13 | VL50, VL51, VL52, VL53 | VC01, VC02, VC03, VC04, VC05

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floor – Standard Center Drain	≥ 0.42	
Shower Floor – Linear Drain	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

PLATINUM: CT70, CT71, CT72, CT73, CT74, CT75, CT76 | PH60, PH61, PH62, PH63 | UB02, UB04 | | SL75, SL76, SL77 | IT50, IT51, IT52 |

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓**
Wet & Level – Interior Floor	≥ 0.42	✓**
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Floor tile and 1x4 mosaic suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic and Wall tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

** Wall tile not suitable for this application

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Wall**: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%. Excluding 4 x 12 option.) **Mosaic:** 1/8"	Medium (V2) PH60, PH61, PH62 & PH63 High (V3) CT70, CT71, CT72, CT73, CT74, CT75, CT76, UB02 & UB04, IT50, IT51, IT52, SL75, SL76 & SL77

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbf	120-230 lbf	> 250 lbf
Scratch Hardness	C1895	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

daltile®

©2026 Daltile (10/26)