STONE LOOK

USAGE

- FLOOR
- WALL
- COUNTERTOP
- SHOWER FLOOR
- EXTERIOR FLOOR

SPECIAL FEATURES

- STEPWISE™
- TRU-EDGE™
- MADE IN THE U.S.A.
- LARGE FORMAT
- MOSAIC/ DECO
- ENCAUSTIC
- TERRAZZO
- PAVER
- CUSTOMIZE
- FLEXFIT™

CG GLAZED CERAMIC

LOW — HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.



CORE FUNDAMENTALS™

PRIME

THE **PRIME TIER** PROVIDES ALL THE ESSENTIAL BENEFITS OF TILE WHILE OFFERING AN ARRAY OF DIFFERENT LOOKS AND DECORATIVE ACCENTS TO HEIGHTEN DESIGN.



CORE FUNDAMENTALS™ – PRIME

GLAZED CERAMIC FLOOR, WALL & MOSAICS

STONE LOOK FINISHES: MATTE & GLOSSY

FLOOR TILE

HEIRLOOM WHITE NS10



LINEAGE GREIGE NS11



HISTORIC GREY NS12

1 x 3 HERRINGBONE MOSAIC



HEIRLOOM WHITE NS10



LINEAGE GREIGE NS11



HISTORIC GREY NS12

AVAILABLE TILE SIZES




18 x 18 Floor Tile | 12 x 24 Floor Tile | 8 x 24 Wall Tile | 1 x 3 Herringbone Mosaic

STONE LOOK FINISHES: MATTE

FLOOR TILE




WHITE BALANS BA30



CHARCOAL BA34

2 x 4 MOSAIC

WHITE BALANS BA30



CHARCOAL BA34

AVAILABLE TILE SIZES



18 x 18 Floor Tile | 12 x 24 Floor Tile | 12 x 12 Floor Tile | 10 x 14 Wall Tile* | 2 x 4 Straight-joint Mosaic

*Only available in BA30.

MONOCHROMATIC LOOK FINISHES: MATTE

FLOOR TILE

RAINIER 1500



BLACK 2011

AVAILABLE TILE SIZES



12 x 12 Floor Tile

CORE FUNDAMENTALS™ – PRIME

GLAZED CERAMIC FLOOR, WALL & MOSAICS

STONE LOOK FINISHES: MATTE

FLOOR TILE


WHITE ELECT EL30


BEIGE ELECT EL31


GREY ELECT EL32

1 x 3 HERRINGBONE MOSAIC


WHITE ELECT EL30


BEIGE ELECT EL31


GREY ELECT EL32

AVAILABLE TILE SIZES



12 x 24
Floor Tile


4 x 12
Wall Tile


1 x 3
Herringbone Mosaic

CONCRETE LOOK FINISHES: MATTE


FLOOR TILE


WHITE KONCRETE KC01


GREY KONCRETE KC04

2 x 2 MOSAIC


WHITE KONCRETE KC01


GREY KONCRETE KC04

AVAILABLE TILE SIZES


18 x 18
Floor Tile


12 x 24
Floor Tile


12 x 12
Floor Tile


2 x 2
Mosaic

STONE LOOK FINISHES: MATTE


FLOOR TILE



VITALITY WHITE RL20



DYNAMIC BEIGE RL21


STAMINA GREY RL23

1.5" HEX MOSAIC


VITALITY WHITE RL20


DYNAMIC BEIGE RL21


STAMINA GREY RL23

AVAILABLE TILE SIZES


12 x 24
Floor Tile


12 x 12
Floor Tile


1.5" Hex
Mosaic

CORE FUNDAMENTALS™ – PRIME

AVAILABLE SIZE & TRIM SHAPES

PRIME

PLEASE REFER TO THE CHART BELOW FOR AVAILABILITY BASED ON COLOR CODE

FLOOR	SIZES		THICKNESS
	**18 x 18 Floor Tile**	17-11/16" x 17-11/16" (45.01 cm x 45.01 cm)	5/16"
	**12 x 24 Floor Tile**	11-13/16" x 23-11/16" (30.02 cm x 60.12 cm)	5/16"
	**12 x 12 Floor Tile**	11-13/16" x 11-13/16" (30.02 cm x 30.02 cm)	5/16"

WALL	SIZES		THICKNESS
	**8 x 24 Wall Tile**	8" x 24" (20.34 cm x 61.30 cm)	3/8"
	**10 x 14 Wall Tile**	9-13/16" x 13-15/16" (24.99 cm x 35.43 cm)	5/16"
	**4 x 12 Wall Tile**	4-1/4" x 12-7/8" (10.88 cm x 32.76 cm)	5/16"

MOSAICS	SIZES		THICKNESS
	**2 x 4 Straight-joint Mosaic Dot-mounted**	12" x 12" Sheet (30.48 x 30.48 cm Sheet)	1/4"
	**2 x 2 Mosaic Dot-mounted**	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"
	**1.5" Hex Mosaic Dot-mounted**	11-3/8 "x 10-1/4" Sheet (28.89 cm x 26.04 cm Sheet)	1/4"
	**1 x 3 Herringbone Mosaic Dot-mounted**	9" x 12" Sheet (22.86 x 30.48 cm Sheet)	1/4"

FLOOR TRIM		
	**P43F9**	3 x 24 Floor Bullnose
	**P43C9**	3 x 12 Floor Bullnose

WALL TRIM		
	S1/212J	12" Jolly
	**S4310**	3 x 10 Wall Bullnose
	**SN4310**	3 x 3 Wall Bullnose Corner

			FLOOR					WALL					MOSAIC			
			FIELD TILE			BULLNOSE		FIELD TILE			BULLNOSE					
COLOR #	COLOR NAME	PAGE #	18 x 18	12 x 24	12 x 12	P43F9	P43C9	10 x 14 Matte	8 x 24 Glossy	4 x 12 Matte	S4310 SN4310	S1/212J	2 x 4 STRAIGHT-JOINT	2 x 2	1.5 HEXAGON	1 x 3 HERRINGBONE
BA30	White Balans	15	●	●	●		●	●			●		●			
BA34	Charcoal	15	●	●	●		●						●			
EL30	White Elect	16		●		●				●		●				●
EL31	Beige Elect	16		●		●				●		●				●
EL32	Grey Elect	16		●		●				●		●				●
KC01	White Koncrete	16	●	●	●		●							●		
KC04	Grey Koncrete	16	●	●	●		●							●		
NS10	Heirloom White	15	●	●			●		●			●				●
NS11	Lineage Greige	15	●	●			●		●			●				●
NS12	Historic Grey	15	●	●			●		●			●				●
RL20	Vitality White	16		●	●	●									●	
RL21	Dynamic Beige	16		●	●	●									●	
RL23	Stamina Grey	16		●	●	●									●	
1500	Rainier	15			●		●									
2011	Black	15			●		●									

CORE FUNDAMENTALS™ – PRIME

APPLICATION SPECIFICATIONS

PRIME: BA30 | BA34 | KC01 | KC04 | NS10 | NS11 | NS12

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓**
Wet & Level – Interior Floor	≥ 0.42	✓**
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

** Wall tile not suitable for this application

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Wall:** 1/16" **Mosaic:** 1/8"	Medium (V2) NS10, NS11 & NS12 High (V3) BA30, BA34, KC01 & KC04

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbf	120-230 lbf	> 250 lbf
Scratch Hardness	C1895	7.0	4.0-6.0	7.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

PRIME: EL30 | EL31 | EL32

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓**
Wet & Level – Interior Floor	≥ 0.42	✓**
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

** Wall tile not suitable for this application

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Wall:** 1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%) **Mosaic:** 1/8"	High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbf	120-230 lbf	> 250 lbf
Scratch Hardness	C1895	8.0	4.0-6.0	7.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

CORE FUNDAMENTALS™ – PRIME

APPLICATION SPECIFICATIONS

PRIME: RL20 | RL21 | RL23

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floor – Standard Center Drain	≥ 0.42	✓*
Shower Floor – Linear Drain	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) **Mosaic:** 1/8"	High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 3.0%
Breaking Strength	C648	> 250 lbf	> 250 lbf
Scratch Hardness	C1895	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

PRIME: 1500 | 2011

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	
Shower Floor – Standard Center Drain	≥ 0.42	
Shower Floor – Linear Drain	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 7.0%
Breaking Strength	C648	> 250 lbf
Scratch Hardness	C1895	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

daltile®

©2026 Daltile (10/26)