



STONE LOOK

COVE CREEK™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL & MOSAIC



 daltile®
IMAGINE WHAT'S POSSIBLE™

COVE CREEK™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL & MOSAIC

Distinguished Linear Graphics Create a Fluid Contemporary Style

With fluid movement in its design, Cove Creek's distinctive stone look creates an impact with elegance and style. Cove Creek impresses with a refined palette of natural colors shown in a light stone graphic with a soft, linear pattern. A diverse mix of sizes and a 2 x 2 mosaic available in essential colors that add character to any design.

- **BALANCE USING NEUTRALS**
 - Serene tones featured in exquisite colors
 - Light stone graphics with a soft, linear pattern add dimension
- **PRACTICAL VERSATILITY**
 - Complete floor, wall and mosaic product line including a 4 x 16 wall tile format
 - 2 x 2 glazed ceramic mosaic is dot-mounted and easy to install



Cover photo features Cove Creek™ Off White 18 x 18 floor tile and 2 x 2 mosaic on the floor with 4 x 16 wall tile on the wall. Above photo features Cove Creek™ Off White 2 x 2 mosaic on the floor and 4 x 16 wall tile on the wall.

STONE LOOK

USAGE



SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES

SIZES:



24 x 24
Floor Tile



18 x 18
Floor Tile



12 x 24
Floor Tile



10 x 14
Wall Tile



4 x 16
Wall Tile



2 x 2
Mosaic

FINISHES: MATTE

GLAZED PORCELAIN FLOOR TILE



OFF WHITE CC08



GRAY CC10

GLAZED CERAMIC WALL TILE



OFF WHITE CC08



GRAY CC10



2 x 2 GLAZED CERAMIC MOSAIC



OFF WHITE CC08



GRAY CC10



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

COVE CREEK™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL & MOSAIC

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Floor Tile	(23-13/16" x 23-13/16") (60.48 cm x 60.48 cm)	5/16"	15.76	4
	18 x 18 Floor Tile	(17-3/4" x 17-3/4") (45.18 cm x 45.18 cm)	5/16"	19.77	9
	12 x 24 Floor Tile	(11-7/8" x 23-5/8") (30.23 cm x 60.12 cm)	5/16"	17.60	9
	10 x 14 Wall Tile	(9-13/16" x 13-15/16") (24.99 cm x 35.40 cm)	5/16"	14.25	15
	4 x 16 Wall Tile	(4" x 16") (10.17 cm x 40.68 cm)	3/8"	13.20	30
	2 x 2 Mosaic (Dot-mounted)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	3/16"	24.00	12

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓†
Wet & Level – Interior Floor	≥ 0.42	✓†
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓†
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

† Wall tile not suitable for this application.


* Mosaic tile only

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)</p> <p>Wall: 10 x 14: 1/16" 4 x 16: 1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)</p> <p>Mosaic: 1/8"</p>	 Random (V4)

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltile.com.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.