

Professional
TILE SOLUTIONS



MOSAIC LOOK

DECORATIVE
ENDEAVORS™
STONE, GLASS & METAL MOSAICS


IMAGINE WHAT'S POSSIBLE™

DECORATIVE

ENDEAVORS™

STONE, GLASS & METAL MOSAICS

On-Trend Confidence

Perfect for a transitional design, this linear mosaic features metal, glass, and stone that adds unassuming confidence to your space. Create an accent wall or limit it to the backsplash to add a hint of color and metallic luster to the kitchen, bathroom, or even outside.

- MIXED MEDIA
 - Stone, glass, and metal blend into a mosaic that stands out without being overbearing
 - Mixed materials add interest to transitional and contemporary designs
- VERSATILE APPLICATION
 - Suitable for walls in all spaces including outdoor applications
 - 13 x 12 mesh-mounted sheets with interlocking edges for a seamless look

MOSAIC LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



MX
MIXED MEDIA

SPECIAL FEATURES



SEE CHARTS FOR FULL PRODUCT DETAILS

Cover photo and above photo feature Endeavors™ Neo Classic 5/8 x random mosaic on the wall.

SIZES:



5/8 x Random
Mosaic

FINISHES: MATTE | GLOSSY

5/8 X RANDOM MOSAIC



AVANT GARDE F163



NEO CLASSIC F164



MYSTIC F161



ZEN F162



SPIRIT F159



MEDITATION F158



SITAR F160



TAMBURA F157



SIMPLICLEAN™

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
	5/8 x Random Mosaic (Mesh-mounted) (13" x 11-7/8" Sheet) (33.00 cm x 30.00 cm Sheet)	5/16"	9.60	10

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Suitable for use in wet areas such as shower walls.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.