



FABRIC ART™

COLORBODY™ PORCELAIN FLOOR & MOSAIC TILE

Inspired by the drape of luxurious textiles, Fabric Art™ uses the weaving mill as a muse, delivering porcelain tile that begs to be touched. Woven, linear and kaleidoscope patterns create a subtle reaction to light and deliver ultimate style for today's modern spaces, bringing your vision to life. Each texture can stand alone as a centerpiece, or serve as a well-orchestrated pairing.



Cover photo features Fabric Art™ Modern Linear Dark Gray 12 x 24 and Modern Kaleidoscope Natural Prism 12 x 24 on the floor.

Above photo features Fabric Art™ Modern Textile Dark Gray, 12x24 and One Quartz Surfaces® Calacatta Lyra on the desk.

FABRIC LOOK

USAGE



LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SPECIAL FEATURES

FABRIC LOOK

FABRIC ART™

COLORBODY™ PORCELAIN FLOOR & MOSAIC TILE

SIZES:

 12 x 24
Floor Tile

 1x3
Straight-joint
Mosaic

FINISHES: MATTE

COLOR PALETTE




WHITE




BEIGE




TAUPE



MEDIUM GRAY




DARK GRAY



MIDNIGHT BLUE

FLOOR TILE – MODERN TEXTILE/MODERN LINEAR



MODERN TEXTILE WHITE MT50



MODERN LINEAR WHITE ML60



MODERN TEXTILE BEIGE MT51




MODERN LINEAR BEIGE ML61



MODERN TEXTILE TAUPE MT52




MODERN LINEAR TAUPE ML62



MODERN TEXTILE MEDIUM GRAY MT53



MODERN LINEAR MEDIUM GRAY ML63



MODERN TEXTILE DARK GRAY MT54



MODERN LINEAR DARK GRAY ML64



MODERN TEXTILE MIDNIGHT BLUE MT55



MODERN LINEAR MIDNIGHT BLUE MT65

FLOOR TILE – MODERN KALEIDOSCOPE



MODERN KALEIDOSCOPE
NATURAL PRISM MK70
Beige/Taupe



MODERN KALEIDOSCOPE
WHITE ASH PRISM MK71
White/Medium Gray/Dark Gray



MODERN KALEIDOSCOPE
ASHEN STEEL PRISM MK72
Medium Gray/Dark Gray




MODERN KALEIDOSCOPE
MIDNIGHT STEEL PRISM MK73
Dark Gray/Midnight Blue

1 x 3 STRAIGHT JOINT MOSAIC TILE (AVAILABLE IN MODERN TEXTILE ONLY)




MODERN TEXTILE
WHITE MT50



MODERN TEXTILE
BEIGE MT51




MODERN TEXTILE
TAUPE MT52



MODERN TEXTILE
MEDIUM GRAY MT53



MODERN TEXTILE
DARK GRAY MT54



MODERN TEXTILE
MIDNIGHT BLUE MT55



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT[™]
*Not Applicable to Mesh-Mounted
Mosaics



CLIMATEPRO™



SIMPLICLEAN™

SIZES

			Thickness	Finish	Made in U.S.A.
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"		
	1 x 3 Straight-joint Mosaic (Mesh-mounted)	11-5/8" x 11-13/16" Sheet (29.61 cm x 29.99 cm Sheet)	5/16"		

Made in the U.S.A. designation is subject to change. Please visit daltile.com for the most current manufacturing information.

 Matte Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors – Standard Center Drain	≥ 0.42	✓*
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Mosaic tile only.

TRIM

Type	Number	Size	Finish
	Bullnose	P43C9	3 x 12 
	Cove Base	P36C9	6 x 12 
	Cove Base Outcorner	PC36C9	1 x 6 

Bullnose in Modern Linear and Modern Kaleidoscope available through Special Order with extended lead time.

 Matte Finish

INSTALLATION

Grout Joint Recommendation

Shade Variation

Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%).



Mosaic Tile: 1/8"

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms 3 All Residential / Light Commercial

2 All Residential Areas 4 All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A1371 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



©2025 Daltile (12/25)