



WALL

**FARRIER**<sup>TM</sup>  
GLAZED CERAMIC



 **daltile**<sup>®</sup>  
IMAGINE WHAT'S POSSIBLE<sup>®</sup>

# FARRIER™

GLAZED CERAMIC

Designed with a hand-crafted clay look, Farrier™ is the essence of old-world charm made anew. Our perfectly-imperfect wall tile collection, featuring uneven surfaces in modular sizes can mix and match to form playful patterns. Explore with rich, earth tones or creamy neutrals – your artisan adventure awaits.



Cover photo features Farrier™ Andalusian Grey 5 x 5 wall tile satin on the shower wall, 2-1/2 x 5 wall tile satin on the arch, and Famed™ Glamour penny round mosaic matte on the shower floor.

Above photo features Farrier™ Grullo 2-1/2 x 5 and Cremello 2-1/2 x 15 satin on the bar with Grullo 2-1/2 x 5 satin on the back wall, Sleigh Creek Carriage 6 x 36 matte on the floor and ONE Quartz Surfaces® Pulsar polished on the countertop.

## WALL

### USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



GLAZED CERAMIC

LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS.

SPECIAL FEATURES

SIZES:



5 x 5  
Wall Tile




2-1/2 x 15  
Wall Tile



2-1/2 x 5  
Wall Tile

FINISHES: SATIN

5 x 5 WALL TILE



CREMELLO FA55



ANDALUSIAN GREY FA56



DARTMOOR GREY FA57



PALOMINO FA58



GRULLO FA60




BLUE ROAN FA59

2-1/2 x 15 WALL TILE



CREMELLO FA55



ANDALUSIAN GREY FA56



DARTMOOR GREY FA57



PALOMINO FA58




GRULLO FA60



BLUE ROAN FA59

2-1/2 x 5 WALL TILE



CREMELLO FA55



ANDALUSIAN GREY FA56



DARTMOOR GREY FA57



PALOMINO FA58



GRULLO FA60



BLUE ROAN FA59



STAINPROOF



DENTPROOF



FIRE-RESISTANT\*



SIMPLICLEAN™

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	5 x 5 Wall Tile	(5-1/16" x 5-1/16") (13.00 cm x 13.00 cm)	5/16" (8.5 mm)	5.43	30
	2-1/2 x 15 Wall Tile	(2-1/2" x 15-1/2") (6.40 cm x 39.50 cm)	5/16" (8.5 mm)	8.16	30
	2-1/2 x 5 Wall Tile	(2-1/2" x 5-1/16") (6.40 cm x 13.00 cm)	5/16" (8.5 mm)	5.34	60

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

## TRIM

Type	Number	Size	Pieces/ Carton
 Jolly	S1/212J	1/2 x 12	20

## INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 Medium (V2)* High (V3)**

\*FA55, FA56, FA58  
\*\*FA57, FA59, FA60

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120 - 230 lbs
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.



All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).

