



MARBLE LOOK

FLORENTINE™

GLAZED PORCELAIN FLOOR TILE & GLAZED CERAMIC WALL AND MOSAIC TILE

 daltile®

FLORENTINE™

GLAZED PORCELAIN FLOOR TILE & GLAZED CERAMIC WALL AND MOSAIC TILE

Florentine™ from Daltile is for those who admire the elegance of marble and stone but desire the durability and low maintenance of ceramic tile. This timeless style mimics the unique tones of marble and stone with a color palette of crisp whites, neutral tans and fresh grays. Transform your area with the Florentine collection.

MARBLE LOOK

USAGE



SPECIAL FEATURES

Cover photo features Florentine™ Nociolla, 12 x 24 on the floor and on the wall. Above photo features Florentine™ Nociolla, 12 x 24 on the floor and wall, with an inset of Argento 12 x 24, Stone A la Mod™ Urban Bluestone oval mosaic border, and Imperial Stone Medallion in the center.

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES:



FINISHES: MATTE | GLOSSY

GLAZED PORCELAIN FLOOR TILE



CARRARA FL06



MARFIL FL07



ARGENTO FL08



NOCIOLLA FL09

GLAZED CERAMIC 2 x 4 MOSAIC TILE



CARRARA FL06



MARFIL FL07



ARGENTO FL08



NOCIOLLA FL09

GLAZED CERAMIC WALL TILE



CARRARA FL06



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FLORENTINE™

GLAZED PORCELAIN FLOOR TILE & GLAZED CERAMIC WALL AND MOSAIC TILE



SIZES

			Thickness	Finish	Made in U.S.A.
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	M	
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	M	
	12 x 12 Floor Tile	11-5/8" x 11-5/8" (29.56 cm x 29.56 cm)	5/16"	M	
	12 x 24 Wall Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	3/8"	G	
	10 x 14 Wall Tile	9-13/16" x 13-3/4" (24.42 cm x 34.83 cm)	5/16"	G	
	2 x 4 Brick-joint Mosaic Tile (Dot-mounted)	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"	M	

Made in the U.S.A. designation is subject to change. Please visit daltile.com for the most current manufacturing information.

M Matte Finish **G** Glossy Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓*
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors - Standard Center Drain	≥ 0.42	✓**
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	✓**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓*
Pool Linings	N/A	✓**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall tile and mosaic suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Floor and mosaic tile only.

** Mosaic tile only.

PRE-CONSUMER RECYCLED MATERIALS

POST-CONSUMER RECYCLED MATERIALS

REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



ZEROTOX

TRIM

	Type	Number	Size	Finish
	Floor Bullnose	S43C9	3 x 12	G
	Wall Bullnose	S43C9	3 x 12	G
	Wall Bullnose	S43C9	3 x 12	G
	Jolly	S1212J	1/2 x 12	G

G Glossy Finish

INSTALLATION

Grout Joint Recommendation

Shade Variation

Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)

12 x 24 Wall Tile: 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)

10 x 14 Wall Tile: 1/16"

2 x 4 Mosaic Tile: 1/8"

High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbf	120-230 lbf	>250 lbf
Scratch Hardness	C1895	8.0	4.0-6.0	4.0-8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltile.com.

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



©2026 Daltile (1/26)