



WOOD LOOK

FLOOR | WALL

**GAINESWOOD™**

GLAZED PORCELAIN

 **daltile®**  
IMAGINE WHAT'S POSSIBLE™

FLOOR | WALL

# GAINESWOOD™

GLAZED PORCELAIN

## Appealing Style With Exceptional Durability

Strike the balance between historic charm and contemporary living with Gaineswood, an essential building block in your design. This easy-living porcelain tile was designed for convenience and durability. Featuring a softly aged, rustic visual in four classic hues, Gaineswood will stand up to your busy lifestyle beautifully.

- DEVELOPED FOR ENDURING STYLE
  - Ideal wood look in easy-to-maintain porcelain tile
  - Perfect for interior spaces with expectancy of water or high traffic
- FEATURES THAT FIT
  - Detailed design in a 6 x 24 size available in four popular colors
  - Easy to install in a staggered brick-joint pattern

WOOD  
LOOK

USAGE



SPECIAL FEATURES

SEE CHARTS FOR FULL  
PRODUCT DETAILS

Above and cover photos feature Gaineswood™ Walnut 6 x 24 on the floor.

SIZES:



FINISHES: MATTE

FLOOR TILE



PINE GW04



HICKORY GW05



ELM GW06



WALNUT GW07



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™  
\*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT™  
\*Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

## SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
	6 x 24 Floor Tile	5/16"	15.00	15
	(6-1/16" x 23-7/8") (15.40 cm x 60.60 cm)			

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	 High (V3)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1 Residential Bathrooms	③	All Residential / Light Commercial
2 All Residential Areas	4	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at [daltile.com/Factors](http://daltile.com/Factors).

Special consideration must be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [daltile.com](http://daltile.com).



All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).