



MOSAIC

IDYLIC BLENDS™
GLASS & STONE



 daltile®
IMAGINE WHAT'S POSSIBLE™

IDYLLIC BLENDS™

GLASS & STONE

The Striking Look of Cubism

Be inspired by the intriguing geometric shapes of Idyllic Blends™. Influenced by cubic art, linear and hexagonal mosaics are pieced together randomly for a visually captivating appearance. Idyllic Blends was designed to stand out, making it perfect for walls and backsplashes. The collection playfully brings together cool undertones and warm shades.

MOSAIC

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES

Cover and above photos feature Idyllic Blends™ Tranquil Snow 2" hexagon mosaic on the backsplash.

SIZES:



2" Hexagon Mosaic



Random Linear Mosaic

FINISHES: GLOSSY

2" HEXAGON MOSAIC



TRANQUIL SNOW IB01



SERENE STORM IB04

RANDOM LINEAR MOSAIC



TRANQUIL SNOW IB01



SERENE STORM IB04



RUSTIC EVE IB03



WATERPROOF



STAINPROOF



SIMPLICLEAN™



VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

IDYLLIC BLENDS™

GLASS & STONE

MOSAIC

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	2" Hexagon Mosaic (Mesh-mounted)	(10-7/8" x 11-1/16" Sheet) (27.60 cm x 28.09 cm Sheet)	3/16"	11.40	15
	Random Linear Mosaic (Mesh-mounted)	(13-7/8" x 11-9/16" Sheet) (35.22 cm x 71.34 cm Sheet)	3/16"	14.40	15

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors - Standard Center Drain (Residential or Commercial)	≥ 0.42	✓*
Shower Floors - Linear Drain	≥ 0.60	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.2 standards.

For additional information refer to "Factors to Consider" at daltille.com/Factors.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.