



CONCRETE LOOK

INDUSTRIAL PARK™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

 **daltile®**
IMAGINE WHAT'S POSSIBLE™

INDUSTRIAL PARK™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

A Modern Mix of Style, Functional Design and Technical Performance

Inspired by terrazzo and concrete, Industrial Park™ asserts itself with solid colors punctuated by randomly placed colored flakes of varying dimension for optimal visual appeal. Industrial Park™ is one of Daltile's growing list of series to feature StepWise™ technology. This patent-pending process combines superior slip resistance with exceptional cleanability making Industrial Park a great choice for commercial applications including ramps. StepWise™ technology and beauty converge delivering solid design and useful function to any space.



CONCRETE
LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER
FLOOR



EXTERIOR
FLOOR



STEPWISE™



TRU-EDGE™



REVEAL
SYNC3D™



MADE IN
THE U.S.A.



LARGE
FORMAT



MOSAIC/
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



P.C.
POLISHED
CONCRETE

LOW

HIGH

SEE CHARTS FOR FULL
PRODUCT DETAILS

SPECIAL FEATURES

Above and cover photos feature Industrial Park™ Light Gray 24 x 24 and Charcoal Gray 24 x 24 on the floor.

CONCRETE LOOK

INDUSTRIAL PARK™

COLORBODY™ PORCELAIN FLOOR
WITH STEPWISE™ TECHNOLOGY

SIZES:



24 x 24
Floor Tile



12 x 24
Floor Tile



12 x 12
Floor Tile

FINISHES: MATTE

COLOR PALETTE



LIGHT
GRAY



CHARCOAL
GRAY



LIGHT GRAY IP07



CHARCOAL GRAY IP09

50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*



FIRE-RESISTANT*



INDOOR/OUTDOOR




















SIMPLICLEAN™


VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

INDUSTRIAL PARK™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

CONCRETE LOOK

SIZES						TRIM				
			Thickness	Finish	Made in U.S.A.		Type	Number	Size	Finish
	24 x 24 Floor Tile	23-13/16" x 23-13/16" (60.48 cm x 60.48 cm)	5/16"				Bullnose	P43C9	3 x 12	
	12 x 24 Floor Tile	11-7/8" x 23-5/8" (30.23 cm x 60.12 cm)	5/16"				Cove Base	P36C9	6 x 12	
	12 x 12 Floor Tile	11-7/8" x 11-7/8" (30.23 cm x 30.23 cm)	5/16"				Cove Base Outcorner	PC36C9	1 x 6	
 Matte Finish						 Matte Finish				

APPLICATIONS			INSTALLATION	
	Target DCOF wet	Suitable	Grout Joint Recommendation	Shade Variation
Dry & Level – Interior Floor	N/A	✓		
Wet & Level – Interior Floor	≥ 0.42	✓		
Shower Floors - Standard Center Drain	≥ 0.42			
Shower Floors - Linear Drain	≥ 0.42 (Mosaic)			
	≥ 0.60 (Floor)	✓*		
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓		
Ramps & Inclines	≥ 0.65	✓		
Walls/Backsplashes	N/A	✓		
Countertops	N/A	✓		
Pool Linings	N/A			
A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF .			3/16"  High (V3)	

PERFORMANCE CHARACTERISTICS		
	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant
For additional information on test results, visit us at: daltile.com/information/TestResults .		

DURABILITY	
Floor Surface Wear Resistance	
1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

NOTES	
Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.	
Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.	
For additional information refer to "Factors to Consider" at: daltile.com/Factors .	
To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.	
Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.	
Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.	