



CONCRETE LOOK

# INDUSTRIAL PARK™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

# INDUSTRIAL PARK™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

## A Modern Mix of Style, Functional Design and Technical Performance

Inspired by terrazzo and concrete, Industrial Park™ asserts itself with solid colors punctuated by randomly placed colored flakes of varying dimension for optimal visual appeal. Industrial Park™ is one of Daltile's growing list of series to feature StepWise™ technology. This patent-pending process combines superior slip resistance with exceptional cleanability making Industrial Park a great choice for commercial applications including ramps. StepWise™ technology and beauty converge delivering solid design and useful function to any space.



### CONCRETE LOOK

#### USAGE



### SPECIAL FEATURES

SEE CHARTS FOR FULL PRODUCT DETAILS

Above and cover photos feature Industrial Park™ Light Gray 24 x 24 and Charcoal Gray 24 x 24 on the floor.

CONCRETE LOOK

# INDUSTRIAL PARK™

COLORBODY™ PORCELAIN  
WITH STEPWISE™ TECHNOLOGY

SIZES:



FINISHES: MATTE

## COLOR PALETTE



LIGHT  
GRAY



CHARCOAL  
GRAY



LIGHT GRAY IP07



CHARCOAL GRAY IP09

**50% MORE**  
SLIP RESISTANT  
THAN ORDINARY TILE<sup>†</sup>

<sup>†</sup>When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT\*



FIRE-RESISTANT\*



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

# INDUSTRIAL PARK™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

CONCRETE LOOK

## SIZES

			Thickness	Finish	Made in U.S.A.
	24 x 24 Floor Tile	(23-13/16" x 23-13/16") (60.48 cm x 60.48 cm)	5/16"		
	12 x 24 Floor Tile	(11-7/8" x 23-5/8") (30.23 cm x 60.12 cm)	5/16"		
	12 x 12 Floor Tile	(11-7/8" x 11-7/8") (30.23 cm x 30.23 cm)	5/16"		

 Matte Finish

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors - Standard Center Drain (Residential or Commercial)	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.42 (Mosaic)	
	≥ 0.60 (Floor)	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	✓
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

## APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

\* 12 x 24 and smaller sizes only.

 **PRE-CONSUMER RECYCLED MATERIALS**

 **MADE IN THE U.S.A.**

 **REVEAL IMAGING®**

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).

## TRIM

	Type	Number	Size	Finish
	Bullnose	P43C9	3 x 12	
	Cove Base	P36C9	6 x 12	
	Cove Base Outcorner	PC36C9	1 x 6	

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	 High (V3)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

CERTIFIED  
**PORCELAIN**  
TILE  
0.0% or less water absorption



**ZEROTOX**

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).

 **daltile**  
IMAGINE WHAT'S POSSIBLE™

©2025 Daltile (1/25)