## IRIDESCENT ISLES<sup>™</sup> GLAZED PORCELAIN WALL TILE WITH REVEALSYNC3D<sup>™</sup>

METALLIC LOOK



AQUA ASIS

# **IRIDESCENT ISLES™**

GLAZED PORCELAIN WALL TILE WITH REVEALSYNC3D™

A stunning tribute to the time-honored Raku firing technique, this series invites you to travel the isles of design excellence. Crafted in a linear 2 x 9 size and six sophisticated hues, the glossy finish and metallic lusters create a captivating allure, enhancing any space with its subtle shimmer. Whether you seek to infuse a sense of serenity or make a bold style statement, Iridescent Isles provides the perfect backdrop for your design aspirations.

AND ALTILE DESIGN

Cover photo features Seaweed,  $2 \times 9$  on the wall. Above photo features Iridescent Isles<sup>™</sup> Seaweed,  $2 \times 9$  on the wall, 0 and Indoterra<sup>™</sup> White Desert,  $6 \times 24$  on the floor.

2 x 9 on the wall, ONE Quartz Surfaces Outer Banks on the fireplace bench

SEE CHARTS FOR FULL PRODUCT DETAILS.

PG

METALLIC

LOOK

3D

\* \* \* \*

# **IRIDESCENT ISLES**<sup>™</sup>

GLAZED PORCELAIN WALL TILE WITH REVEALSYNC3D™





### COLOR PALETTE













ANCHOR

SEASHELL

COVE

TREASURE

SEAWEED

GLAZED PORCELAIN WALL TILE



COVE IR21

SEASHELL IR20



TREASURE IR25



SEAWEED IR23



HARBOR IR24



ANCHOR IR22



VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

# **IRIDESCENT ISLES**<sup>™</sup>

GLAZED PORCELAIN WALL TILE WITH REVEALSYNC3D™

## METALLIC LOOK

#### SIZES

		Thickness	Finish	Made in U.S.A.
2 x 9 Wall Tile	2-1/4" x 9-1/2" (6.00 cm x 24.60 cm)	3/8"	G	**

G Glossy Finish

#### APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	~
Countertops	N/A	
Pool Linings	N/A	~

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest<sup>™</sup>, visit daltile.com/DCOF.

#### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

#### INSTALLATION



### PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	7.0
Chemical Resistance	C650	Resistant
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

#### NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltile.com



### REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.





7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile<sup>®</sup> products and information, visit our website at **daltile.com**.

