

WALL

LUMINIQUE™
GLAZED CERAMIC WALL TILE & MOSAIC



LUMINIQUE™

GLAZED CERAMIC WALL TILE & MOSAIC

Elevate your space with Luminique, designed to infuse vibrant hues and rich texture into any room. This series brings depth, personality, and visual intrigue to walls, backsplashes, and accent areas. Whether you're looking for a bold statement or a subtle pop of color, Luminique offers versatile options to suit your style. Discover the creative possibilities of Luminique—where color and texture come together to make a lasting impression.



Cover photo features Luminique™ Navy, 12 x 24 Fluted on the wall.
Above photo features Luminique™ Dune, 12 x 24 Hand Crafted on the wall and Panoramic Porcelain Surfaces™ Calacatta Aries on the countertop.

WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



REVEAL SYNC3D™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



C-CERTIFIED



LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES

SIZES:



12 x 24
Wall Tile




2 x 5 Framed
Mosaic Tile

FINISHES: GLOSSY

WALL TILE



ARCTIC WHITE 0190



DUNE 0184



JUNIPER 0185



NAVY K189

FLUTED WALL TILE



ARCTIC WHITE 0190



DUNE 0184



JUNIPER 0185



NAVY K189

CIRCLE WALL TILE



ARCTIC WHITE 0190



DUNE 0184



JUNIPER 0185




NAVY K189


WEAVE WALL TILE




ARCTIC WHITE 0190



DUNE 0184



JUNIPER 0185



NAVY K189


FRAMED PICKET MOSAIC TILE




ARCTIC WHITE 0190



DUNE 0184



JUNIPER 0185



NAVY K189



STAINPROOF



DENTPROOF



FIRE-RESISTANT







SIMPLICLEAN™


LUMINIQUE™

GLAZED CERAMIC WALL TILE & MOSAIC

WALL

SIZES

			Thickness	Finish
	12 x 24 Wall Tile	11-3/4" x 23-3/4" (29.92 cm x 60.43 cm)	5/16"	
	2 x 5 Framed Picket Mosaic Tile (Dot-mounted)	11-1/8" x 12-1/4" Sheet (28.25 cm x 31.11 cm Sheet)	1/4"	

 Glossy Finish

PERFORMANCE CHARACTERISTICS

	ASTM#	Wall Result	Mosaic Result
Water Absorption	C373	< 20.0%	< 3.0%
Breaking Strength	C648	120 - 230 lbf	> 250 lbf
Scratch Hardness	C1895	4.0 - 6.0	4.0 - 6.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	✓*



A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Wall and mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.


* Mosaic tile only.

TRIM

Type	Number	Size	Finish
 Jolly	S1/212J	1/2 x 12	

 Glossy Finish

INSTALLATION

Grout Joint Recommendation	Shade Variation
Wall Tile: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%. Use straight-joint only when using the same pattern.)	 Medium (V2)
Mosaic Tile: 1/8"	

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

 **PRE-CONSUMER RECYCLED MATERIALS**

 **POST-CONSUMER RECYCLED MATERIALS**

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



ZEROTOX

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

 **daltile®**

IMAGINE WHAT'S POSSIBLE™

©2025 Daltile (05/25)