



MOSAIC

WALL
MARVEL™
STONE & GLASS MOSAIC



 **daltile®**
IMAGINE WHAT'S POSSIBLE™

Gaze at the Beauty of Marvel

Stand in awe at the wonder of the Marvel mosaics. This distinctive collection is comprised of a blend of stone and glass. Its broad color palette is made up of 12 unique blends.

- UNCOMMON ALLURE
 - Distinctive blend of stone and glass
 - Available in 12 unique blends
- PICTURESQUE DÉCOR
 - Broad color palette comprising both bright and neutral combinations
 - Use to create dazzling accent walls or colorful backsplashes



MOSAIC

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRI-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



MX

LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

SIZES:



FINISHES: GLOSSY

MOSAIC




OPAL MV24



WHIMSICAL MV20




GEMSTONE MV29



RADIANCE MV30




ALLURE MV27



ARTISTRY MV26



CHARM MV23



RUBY MV31




WONDER MV28



ILLUSION MV25



MYSTIQUE MV21



ONYX MV22



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT*
*Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™



SIMPLICLEAN™

SIZES

	Thickness	Sq. Ft./ Carton	Pieces/ Carton
 5/8 x 5/8 Mosaic (Mesh-mounted on 12" x 12" Sheet)	5/16"	11.00	11
(11-7/8" x 11-7/8" Sheet) (30.00 cm x 30.00 cm Sheet)			

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.2 standards.

For additional information refer to "Factors to Consider" at daltille.com/Factors.

 **PRE-CONSUMER RECYCLED MATERIALS**

All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.