

CONCRETE LOOK

MERCHANT™
GLAZED PORCELAIN









COLOR PALETTE









GLAZED PORCELAIN









POWDER MR32

















MERCHANT™ **GLAZED PORCELAIN**

SIZES

		Thickness	Finish
33 x 33 Floor Tile	(33-1/6" x 33-1/6") (84.00 cm x 84.00 cm)	5/16"	M



PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

APPLICATIONS

Target DCOF wet	Suitable
N/A	~
≥ 0.42	~
≥ 0.42	
≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	• • • • • • • • • • • • • • • • • • • •
≥ 0.60	
≥ 0.65	
N/A	✓
N/A	✓
N/A	
	DCOF wet N/A ≥ 0.42 ≥ 0.42 (Mosaic) ≥ 0.60 (Floor) ≥ 0.65 N/A N/A

A DCOF value of ≥0.42 is the Standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation	
1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	Medium (V2)	

DURABILITY						
Floor Surface Wear Resistance						
1	Residential Bathrooms	3	All Residential / Light Commercial			
2	All Residential Areas	4	All Residential / Commercial			

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex $\,$ modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com







