



| SIZES:

□ 10 x 14 Wall Tile

FINISHES: GLOSSY







WALL TILE

WHITE



GLOSS WHITE PLO2









FIRE-RESISTANT



SIZES

		Thickness	Finish
10 x 14 Wall Tile	9-13/16" x 13-15/16" (24.99 cm x 35.43 cm)	5/16"	•



APPLICATIONS

Target DCOF wet	Suitable
N/A	
≥ 0.42	
≥ 0.42	
≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
≥ 0.60	
≥ 0.65	
N/A	✓
N/A	
N/A	
	DCOF wet N/A ≥ 0.42 ≥ 0.42 ≥ 0.42 (Mosaic) ≥ 0.60 (Floor) ≥ 0.65 N/A N/A

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest", visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

LRV & MUNSELL

Color #	LRV Illuminate-OBS: F02-02 (CWF)	Munsell
PL02	83.9	7.0Y 9.2/0.2

TRIM

Туре	Number	Size	Finish
Bullnose (10" side)	S4310	3 × 10	6
Bullnose Corner	SN4309	3 x 3	G



INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16"	Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbf
Scratch Hardness	C1895	4.0-6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



