

WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER
FLOOR



EXTERIOR
FLOOR



STEPWISE™



TRU-EDGE™



REVEAL
SYNC3D™



MADE IN
THE U.S.A.



LARGE
FORMAT



MOSAIC/
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



\$ LOW HIGH

SEE CHARTS FOR
FULL PRODUCT
DETAILS.

SIZES:

10 x 14
Wall Tile

FINISHES: GLOSSY

COLOR PALETTE



WHITE

WALL TILE



GLOSS WHITE PLO2



STAINPROOF



DENTPROOF





FIRE-RESISTANT*



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Finish
	10 x 14 Wall Tile	9-13/16" x 13-15/16" (24.99 cm x 35.43 cm)	5/16"	

 Glossy Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.





APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

LRV & MUNSELL


Color #	LRV Illuminate-OBS: F02-02 (CWF)	Munsell
PL02	83.9	70Y 9.2/0.2

TRIM

Type	Number	Size	Finish
 Bullnose (10" side)	S4310	3 x 10	
 Bullnose Corner	SN4309	3 x 3	

 Glossy Finish

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16" (Features a lugged edge that creates an automatic 1/16" grout joint.)	 Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	≥ 125 lbf
Scratch Hardness	C1895	≥ 4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

PRE-CONSUMER
RECYCLED MATERIALSPOST-CONSUMER
RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.

