

5.0mm | 20 mil

# MULTIMEDIA™ CONCRETE

FLEXIBLE GLUE DOWN

PROSERIES™  
VITACORE RESILIENT FLOORING

 daltile



 VitaCore™  
PVC FREE



TitanGuard™

5.0mm | 20 mil

# MULTIMEDIA™ CONCRETE

FLEXIBLE GLUE DOWN

Multimedia Concrete, a contemporary look, brings the sleek, industrial aesthetic of poured concrete into refined glue-down resilient flooring. Available in four colors, this series offers a minimalist palette designed to elevate modern commercial interiors, from open-concept offices to hospitality spaces and beyond. Subtle embossing adds tactile interest, while its durable 20 mil wear layer provides lasting performance in high-traffic environments. Discover the modern edge of Multimedia Concrete, just one of many inspired surfaces within the Multimedia Collection.

## CONTEMPORARY & SUSTAINABLE

- Constructed using Vitacore™, an innovative PVC-free material made from recycled content
- 20 mil wear layer for heavy commercial applications
- Embossed
- TitanGuard™ Technology
- 100% Waterproof



Cover photo features Multimedia™ Concrete Poppy, 18 x 18 on the floor.

Above photo features Multimedia™ Concrete Chai, 18 x 36 on the floor, Bee Hive Medley™ Cube Negative, 8-1/2 x 10 Hexagon on the bar and wall, and Panoramic Porcelain Surfaces™ Anthracite on the table tops and counter.

5.0mm | 20 mil

# MULTIMEDIA™ CONCRETE

FLEXIBLE GLUE DOWN

SIZES:



18 x 36  
Floor



18 x 18  
Floor

## 18 x 36 FLOOR SIZE



PEONY  
MC80



CHAI  
MC81



JASMINE  
MC82



POPPY  
MC83

## 18 x 18 FLOOR SIZE



PEONY  
MC80



CHAI  
MC81



JASMINE  
MC82



POPPY  
MC83

5.0mm | 20mil

# MULTIMEDIA™ CONCRETE

FLEXIBLE GLUE DOWN



NOISE REDUCING



EASY TO CLEAN



100% WATERPROOF

SPECIFICATIONS	18" x 18"	18" x 36"
Product Type:	Resilient Flooring Dry Back	Resilient Flooring Dry Back
Installation:	Glue Down	Glue Down
Thickness:	5.0 mm	5.0 mm
Wear Layer:	20 Mil (0.508)	20 Mil (0.508)
Finish:	TitanGuard™ Technology	TitanGuard™ Technology
Size:	18" W x 18" L	18" W x 36" L
Underlayment:	N/A	N/A
Bevel:	Beveled	Beveled
Embossing:	Embossed	Embossed
Plank Variation:	12 pcs / 27 SF	6 pcs / 27 SF
Sq. Ft./Carton:	27	27
Pieces/Carton:	12 pcs / carton	6 pcs / carton
Weight	4.4 lbs per pc / 52.80 lbs per pc	8.8 lbs per pc / 52.80 lbs per carton
Warranty:	Limited Lifetime Residential Warranty Limited 30 Year Multifamily Warranty Limited 30 Year Light Commercial Warranty Limited 20 Year Commercial Warranty Limited 10 Year Heavy Commercial Warranty	Limited Lifetime Residential Warranty Limited 30 Year Multifamily Warranty Limited 30 Year Light Commercial Warranty Limited 20 Year Commercial Warranty Limited 10 Year Heavy Commercial Warranty
Installation Advisory:	Glue Down Resilient Flooring must be installed using Daltile's recommended adhesives. See <a href="http://daltile.com/multimedia-collection">daltile.com/multimedia-collection</a> for more information.	
Stocking Platform:	5.0 mm   20 mil	
Special order Platform:	Additional platforms available on special order. Minimum quantities apply. Contact your Daltile representative for additional information.	

## PERFORMANCE & CHARACTERISTICS

Construction:	PVC Free Resilient Flooring
Classification:	ASTM F1700 - Class III, Type B Embossed
Squareness:	ASTM F2421 - Passes - ± 0.010" max
Size and Tolerance:	ASTM F2421 - Passes - ± 0.024 in.
Thickness:	ASTM 386/387 - Passes - ± 0.199 in.
Flexibility:	ASTM F137 - Passes - 1" mandrel, no crack or break
Dimensional Stability:	ASTM F2199 - Passes - L: -0.007 W: -0.006
Static Load Limit:	ASTM F970 - Passes - Average = 0.003 in.
Residual Indentation:	ASTM F1914 - Passes - 4.76%
Resistance To Chemicals:	ASTM F925 - Passes - No change observed
Resistance To Light:	ASTM F1515 - Passes - ΔE < 8.0
Resistance To Heat:	ASTM F1514 - Passes - Average ΔE < 8.0
Critical Radiant Flux:	ASTM E648 - Passes - Class 1 (> 0.45w/cm2)
Smoke Density:	ASTM E662 - Part A - Passes - <450 W/cm2

## NOTES

See [daltile.com](http://daltile.com) for recommended installation and care guidelines.



7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com)



©2026 Dal-Tile, LLC (06/26)