

5.0mm | 20 mil

MULTIMEDIA™ FABRIC

FLEXIBLE GLUE DOWN

PROSERIES™
LUXURY VINYL FLOORING

 daltile



 VitaCore™
PVC FREE VINYL



TitanGuard™

5.0mm | 20 mil

MULTIMEDIA™ FABRIC

FLEXIBLE GLUE DOWN

Multimedia Fabric brings an unexpected and sophisticated textile aesthetic to luxury vinyl flooring; delivering a look you won't find anywhere else. With a palette of moody, modern colorways and a richly embossed texture, this glue-down flooring solution is perfect for spaces seeking depth, character, and style. Discover Multimedia Fabric, one of many bold, inspired options in the ever-evolving Multimedia Collection.

SOPHISTICATED & SUSTAINABLE

- Constructed using Vitacore™, an innovative PVC-free material made from recycled content
- 20 mil wear layer for heavy commercial applications
- Embossed
- TitanGuard™ Technology
- 100% Waterproof



Cover photo features Multimedia™ Fabric, Velvet, 18 x 36 on the outer floor and Multimedia™ Terrazzo, Lake, 18 x 18 in the inner floor. Above photo features Cashmere, 9 x 72 on the floor.

5.0mm | 20 mil
MULTIMEDIA™ FABRIC
FLEXIBLE GLUE DOWN

SIZES:



9 x 72
Floor Tile



18 x 36
Floor Tile

9 x 72 FLOOR SIZE (SHOWN IN GRID)



COTTON MF40



CASHMERRE MF41




WOOL MF42



GEORGETTE MF43



MODAL MF44



VELVET MF45


18 x 36 FLOOR SIZE



COTTON MF40



CASHMERRE MF41



WOOL MF42



GEORGETTE MF43



MODAL MF44



VELVET MF45

5.0mm | 20mil

MULTIMEDIA™ FABRIC

FLEXIBLE GLUE DOWN



NOISE REDUCING



EASY TO CLEAN



100% WATERPROOF



100% VIRGIN VINYL

SPECIFICATIONS

9" x 72"

18" x 36"

Product Type:	LVF Dry Back	LVF Dry Back
Installation:	Glue Down	Glue Down
Thickness:	5.0 mm	5.0 mm
Wear Layer:	20 Mil (0.508)	20 Mil (0.508)
Finish:	TitanGuard™ Technology	TitanGuard™ Technology
Size:	9" W x 72" L	18" W x 36" L
Underlayment:	N/A	N/A
Bevel:	Beveled	Beveled
Embossing:	Embossed	Embossed
Plank Variation:	4 pcs / 18 SF	4 pcs / 18 SF
Sq. Ft./Carton:	27	27
Pieces/Carton:	6 pcs/carton	6 pcs/carton
Weight	8.8 lbs per pc/ 52.80 lbs per carton	8.8 lbs per pc/ 52.80 lbs per carton
Warranty:	Limited Lifetime Residential Warranty Limited 30 Year Multifamily Warranty Limited 30 Year Light Commercial Warranty Limited 20 Year Commercial Warranty Limited 10 Year Heavy Commercial Warranty	Limited Lifetime Residential Warranty Limited 30 Year Multifamily Warranty Limited 30 Year Light Commercial Warranty Limited 20 Year Commercial Warranty Limited 10 Year Heavy Commercial Warranty
Installation Advisory:	Please refer to the LVF glue down installation guide for adhesive recommendations, available on daltile.com/LVF	
Stocking Platform:	5.0 mm 20 mil	
Special order Platform:	Additional platforms available on special order. Minimum quantities apply. Contact your Daltile representative for additional information.	

PERFORMANCE & CHARACTERISTICS

Construction:	Commercial Grade Luxury Vinyl Flooring; 100% Virgin Vinyl
Classification:	ASTM F1700 - Class III, Type B Embossed
Squareness:	ASTM F2421 - Passes - ± 0.010" max
Size and Tolerance:	ASTM F2421 - Passes - ± 0.024 in.
Thickness:	ASTM 386/387 - Passes - ± 0.199 in.
Flexibility:	ASTM F137 - Passes - 1" mandrel, no crack or break
Dimensional Stability:	ASTM F2199 - Passes - L: -0.007 W: -0.006
Static Load Limit:	ASTM F970 - Passes - Average = 0.003 in.
Residual Indentation:	ASTM F1914 - Passes - 4.76%
Resistance To Chemicals:	ASTM F925 - Passes - No change observed
Resistance To Light:	ASTM F1515 - Passes - ΔE < 8.0
Resistance To Heat:	ASTM F1514 - Passes - Average ΔE < 8.0
Critical Radiant Flux:	ASTM E648 - Passes - Class 1 (> 0.45w/cm2)
Smoke Density:	ASTM E662 - Part A - Passes - <450 W/cm2

NOTES

See daltile.com/LVF for recommended installation and care guidelines.



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com/LVF

PROSERIES™
LUXURY VINYL FLOORING



©2026 Dal-Tile, LLC (03/26)