

5.0mm | 20 mil

# MULTIMEDIA™ STONE

FLEXIBLE GLUE DOWN

# PROSERIES™

VITACORE RESILIENT FLOORING

 daltile



 VitaCore™  
PVC FREE



TitanGuard™

5.0mm | 20 mil

# MULTIMEDIA™ STONE

FLEXIBLE GLUE DOWN

Multimedia Stone brings the natural beauty of stone to glue down resilient flooring. Featuring a palette of soft neutrals and subtle veining, this series offers a clean, sophisticated look that complements a wide range of commercial interiors, all with the ease of installation and long-term performance. Explore the quiet strength of Multimedia Stone; one of many inspired surfaces within the ever-evolving Multimedia Collection.

## MINIMAL & SUSTAINABLE

- Constructed using Vitacore™, an innovative PVC-free material made from recycled content
- 20 mil wear layer for heavy commercial applications
- Embossed
- TitanGuard™ Technology
- 100% Waterproof



Cover photo features Multimedia™ Stone Sand, 18 x 36 on the floor.  
Above photo features Multimedia™ Stone Coal, 18 x 36 on the floor.

5.0mm | 20 mil  
**MULTIMEDIA™ STONE**  
FLEXIBLE GLUE DOWN

SIZES:



9 x 72  
Floor



18 x 36  
Floor

9 x 72 FLOOR SIZE (SHOWN IN GRID)



SALT MT20



SAND MT21



BASIN MT22



COAL MT23

18 x 36 FLOOR SIZE



SALT MT20



SAND MT21



BASIN MT22



COAL MT23

5.0mm | 20mil

# MULTIMEDIA™ STONE

FLEXIBLE GLUE DOWN



NOISE REDUCING



EASY TO CLEAN



100% WATERPROOF

## SPECIFICATIONS

9" x 72"

18" x 36"

Product Type:	Resilient Flooring Dry Back	Resilient Flooring Dry Back
Installation:	Glue Down	Glue Down
Thickness:	5.0 mm	5.0 mm
Wear Layer:	20 Mil (0.508)	20 Mil (0.508)
Finish:	TitanGuard™ Technology	TitanGuard™ Technology
Size:	9" W x 72" L	18" W x 36" L
Underlayment:	N/A	N/A
Bevel:	Beveled	Beveled
Embossing:	Embossed	Embossed
Plank Variation:	8 pcs / 36 SF	8 pcs / 36 SF
Sq. Ft./Carton:	27	27
Pieces/Carton:	6 pcs / carton	6 pcs / carton
Weight	8.8 lbs per pc / 52.80 lbs per carton	8.8 lbs per pc / 52.80 lbs per carton
Warranty:	Limited Lifetime Residential Warranty Limited 30 Year Multifamily Warranty Limited 30 Year Light Commercial Warranty Limited 20 Year Commercial Warranty Limited 10 Year Heavy Commercial Warranty	Limited Lifetime Residential Warranty Limited 30 Year Multifamily Warranty Limited 30 Year Light Commercial Warranty Limited 20 Year Commercial Warranty Limited 10 Year Heavy Commercial Warranty
Installation Advisory:	Glue Down Resilient Flooring must be installed using Daltile's recommended adhesives. See <a href="http://daltile.com/multimedia-collection">daltile.com/multimedia-collection</a> for more information.	
Stocking Platform:	5.0 mm   20 mil	
Special order Platform:	Additional platforms available on special order. Minimum quantities apply. Contact your Daltile representative for additional information.	

## PERFORMANCE & CHARACTERISTICS

Construction:	PVC Free Resilient Flooring
Classification:	ASTM F1700 - Class III, Type B Embossed
Squareness:	ASTM F2421 - Passes - ± 0.010" max
Size and Tolerance:	ASTM F2421 - Passes - ± 0.024 in.
Thickness:	ASTM 386/387 - Passes - ± 0.199 in.
Flexibility:	ASTM F137 - Passes - 1" mandrel, no crack or break
Dimensional Stability:	ASTM F2199 - Passes - L: -0.007 W: -0.006
Static Load Limit:	ASTM F970 - Passes - Average = 0.003 in.
Residual Indentation:	ASTM F1914 - Passes - 4.76%
Resistance To Chemicals:	ASTM F925 - Passes - No change observed
Resistance To Light:	ASTM F1515 - Passes - ΔE < 8.0
Resistance To Heat:	ASTM F1514 - Passes - Average ΔE < 8.0
Critical Radiant Flux:	ASTM E648 - Passes - Class 1 (> 0.45w/cm2)
Smoke Density:	ASTM E662 - Part A - Passes - <450 W/cm2

## NOTES

See [daltile.com](http://daltile.com) for recommended installation and care guidelines.



CERTIFIED BY SCS Global Services



7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com)

PROSERIES™

VITACORE RESILIENT FLOORING



©2026 Dal-Tile, LLC (06/26)