

5.0mm | 20 mil

# MULTIMEDIA™ WOOD

FLEXIBLE GLUE DOWN

# PROSERIES™

VITACORE RESILIENT FLOORING

 daltile



 VitaCore™  
PVC FREE



TitanGuard™

5.0mm | 20 mil

# MULTIMEDIA™ WOOD

FLEXIBLE GLUE DOWN

Multimedia Wood blends modern style with nostalgic charm. This series offers a fresh take on classic wood visuals, featuring sleek, linear 9" x 72" planks alongside decorative 18" x 18" parquet designs. Each piece is embossed for texture and visual depth. Designed for easy glue-down installation, Multimedia Wood brings effortless style to any commercial space. Explore the creative range of Multimedia Wood, just one of the many inspired design solutions within the Multimedia Collection.

## EFFORTLESS & SUSTAINABLE


- Constructed using Vitacore™, an innovative PVC-free material made from recycled content
- Flexible Glue Down
- 20 mil wear layer for heavy commercial applications
- Embossed
- TitanGuard™ Technology
- 100% Waterproof



Cover photo features Multimedia™ Wood Nook and Thistle, 9 x 72 on the floor.  
Above photo features Multimedia™ Wood Thistle 9 x 72 on the outer floor and 18 x 18 on the inner floor.

5.0mm | 20 mil  
**MULTIMEDIA™ WOOD**  
FLEXIBLE GLUE DOWN

SIZES:



9 x 72 WOOD LOOK PLANKS (SHOWN IN GRID)



RISE MW30



NOOK MW31



THISTLE MW32



HOLLOW MW33



CREST MW34



BRIAR MW35

18 x 18 WOOD PARQUET DECO



RISE MW30



NOOK MW31



THISTLE MW32



HOLLOW MW33



CREST MW34



BRIAR MW35

5.0mm | 20mil

# MULTIMEDIA™ WOOD

FLEXIBLE GLUE DOWN



NOISE REDUCING



EASY TO CLEAN



100% WATERPROOF

## SPECIFICATIONS

9" x 72"

18" x 18"

Product Type:	Resilient Flooring Dry Back	Resilient Flooring Dry Back
Installation:	Glue Down	Glue Down
Thickness:	5.0 mm	5.0 mm
Wear Layer:	20 Mil (0.508)	20 Mil (0.508)
Finish:	TitanGuard™ Technology	TitanGuard™ Technology
Size:	9" W x 72" L	18" W x 18" L
Underlayment:	N/A	N/A
Bevel:	Beveled	Beveled
Embossing:	Embossed	Embossed
Plank Variation:	4 pcs / 18 SF	6 pcs / 13.5 SF
Sq. Ft./Carton:	27	27
Pieces/Carton:	6 pcs / carton	12 pcs / carton
Weight	8.8 lbs per pc / 52.80 lbs per carton	4.4 lbs per pc / 52.80 lbs per carton
Warranty:	Limited Lifetime Residential Warranty Limited 30 Year Multifamily Warranty Limited 30 Year Light Commercial Warranty Limited 20 Year Commercial Warranty Limited 10 Year Heavy Commercial Warranty	Limited Lifetime Residential Warranty Limited 30 Year Multifamily Warranty Limited 30 Year Light Commercial Warranty Limited 20 Year Commercial Warranty Limited 10 Year Heavy Commercial Warranty
Installation Advisory:	Glue Down Resilient Flooring must be installed using Daltile's recommended adhesives. See <a href="http://daltile.com/multimedia-collection">daltile.com/multimedia-collection</a> for more information.	
Stocking Platform:	5.0 mm   20 mil	
Special order Platform:	Additional platforms available on special order. Minimum quantities apply. Contact your Daltile representative for additional information.	

## PERFORMANCE & CHARACTERISTICS

Construction:	PVC Free Resilient Flooring
Classification:	ASTM F1700 - Class III, Type B Embossed
Squareness:	ASTM F2421 - Passes - ± 0.010" max
Size and Tolerance:	ASTM F2421 - Passes - ± 0.024 in.
Thickness:	ASTM 386/387 - Passes - ± 0.199 in.
Flexibility:	ASTM F137 - Passes - 1" mandrel, no crack or break
Dimensional Stability:	ASTM F2199 - Passes - L: -0.007 W: -0.006
Static Load Limit:	ASTM F970 - Passes - Average = 0.003 in.
Residual Indentation:	ASTM F1914 - Passes - 4.76%
Resistance To Chemicals:	ASTM F925 - Passes - No change observed
Resistance To Light:	ASTM F1515 - Passes - ΔE < 8.0
Resistance To Heat:	ASTM F1514 - Passes - Average ΔE < 8.0
Critical Radiant Flux:	ASTM E648 - Passes - Class 1 (> 0.45w/cm2)
Smoke Density:	ASTM E662 - Part A - Passes - <450 W/cm2

## NOTES

See [daltile.com](http://daltile.com) for recommended installation and care guidelines.



7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com)



©2026 Dal-Tile, LLC (06/26)