

QUARRY TEXTURES™

QUARRY TILE

QUARRY

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



QUARRY



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

ASHEN GRAY OT03

ABRASIVE SURFACE




ASHEN GRAY OT03 (2)

SMOOTH SURFACE



ASHEN GRAY OT03 (2)

FLASH



ASHEN FLASH OT04 (2)

SIZES:



8 x 8
Floor Tile




6 x 6
Floor Tile

FINISHES: MATTE | TEXTURED

DIABLO RED OT01

ABRASIVE SURFACE



DIABLO RED OT01 (1)

SMOOTH SURFACE



DIABLO RED OT01 (1)

FLASH



RED FLASH OT02 (1)

SIZES:




8 x 8
Floor Tile

FINISHES: MATTE | TEXTURED


HARVEST RED BLEND OQ70

ABRASIVE SURFACE



HARVEST RED BLEND OQ70 (1)

SMOOTH SURFACE



HARVEST RED BLEND OQ70 (1)

SIZES:



6 x 6
Floor Tile

FINISHES: MATTE | TEXTURED



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



INDOOR/OUTDOOR



SIMPLICLEAN™



QUARRY

ASHEN GRAY, DIABLO RED, ASHEN FLASH & RED FLASH

QUARRY TEXTURES™

QUARRY TILE

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	8 x 8 Floor Tile	(8" x 8") (20.30 cm x 20.30 cm)	1/2"	11.11	25
	6 x 6 Floor Tile	(6" x 6") (15.20 cm x 15.20 cm)	1/2"	11.00	44

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Commercial)	≥ 0.42	✓**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	✓*
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Suitable for industrial installation requiring high compressive strength.

Subject to Oils: Absorbs oils, grease and other liquids to keep floors slip-resistant, yet does not contaminate the surface. Proper cleaning methods easily remove any contaminants that do get absorbed into the tile.

* Abrasive surface only

** 6 x 6 only

PERFORMANCE CHARACTERISTICS










	ASTM#	Result
Water Absorption	C373	< 3.0%
Breaking Strength	C648	> 400 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/8"	 High (V3) - non-Flash colors  Random (V4) - Flash colors

TRIM

	Type	Number	Size	Pieces/ Carton
	Bullnose	Q1665†	6 x 6	44
	Bullnose Corner	QCRL1665†	6 x 6	44
	Cove Base	Q3585▲	5 x 8	24
	Round Top Cove Base	Q3565▲	5 x 6	44
	Round Top Cove Base Corner Right	QCR3565▲	5 x 6	20
	Round Top Cove Base Corner Left	QCL3565▲	5 x 6	20
	Cove Base Inside Corner	QB3565▲	1 x 5	25
	Bullnose	Q1885*	8 x 8	25
	Bullnose Corner	QCRL1885*	8 x 8	25

Bullnose, cove base and cove base corner trim are intended to coordinate with floor tile in the standard 90-degree installation position.

† Available in smooth, abrasive, and flash.

▲ Available in smooth only.

* Available in smooth and flash.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Special care should be taken when grouting; a grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface.

It is necessary to follow the proper procedures and recommendations from the grout and maintenance products' manufacturers.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.




QUARRY

HARVEST RED BLEND

QUARRY TEXTURES™

QUARRY TILE

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	6 x 6 Floor Tile	(6" x 6") (15.20 cm x 15.20 cm)	3/8"	10.78	44

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Commercial)	≥ 0.42	✓
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	✓*
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Suitable for industrial installation requiring high compressive strength.

Subject to Oils: Absorbs oils, grease and other liquids to keep floors slip-resistant, yet does not contaminate the surface. Proper cleaning methods easily remove any contaminants that do get absorbed into the tile.

* Abrasive surface only

PERFORMANCE CHARACTERISTICS



	ASTM#	Result
Water Absorption	C373	< 3.0%
Breaking Strength	C648	> 400 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/8"	 Random (V4)

TRIM

	Type	Number	Size	Pieces/ Carton
	Bullnose	Q1665 ▲	6 x 6	44
	Round Top Cove Base	Q3665 ▲	6 x 6	12
	Cove Base Inside Corner	QB3665 ▲	1 x 6	40
	Cove Base Outside Corner	QC3665 ▲	1 x 6	20

Bullnose, cove base and cove base corner trim are intended to coordinate with floor tile in the standard 90-degree installation position.

▲ Trim is not available with abrasive.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Special care should be taken when grouting; a grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface.

It is necessary to follow the proper procedures and recommendations from the grout and maintenance products' manufacturers.

ZEROTOX
Healthy Homes | Healthy Planet



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.

daltile®
IMAGINE WHAT'S POSSIBLE™
©2023 Daltile (12/23)