

Professional  
TILE SOLUTIONS



MOSAIC

DECORATIVE  
**REGAL PENDANT™**  
GLASS & STONE MOSAICS

 **dalTile®**  
IMAGINE WHAT'S POSSIBLE™

DECORATIVE

# REGAL PENDANT™

GLASS & STONE MOSAICS

## Captivate With Luminous Geometric Designs

A collection made to shine, Regal Pendant™ channels nostalgic grandeur. Inspired by the beauty of stained glass, a trapezoid mosaic design awes in both iridescent glass and natural stone shades. Alternating frosted and metallic finishes accentuate the collection's radiance and luxury. Regal Pendant brings the drama of wall design possibility to life.

- **EVOKES GLAMOUR**
  - Crafted from glass and natural stone
  - Multiple finishes add dynamic style
  - Perfect for creating walls that make a statement
- **DRAMATIC DETAIL**
  - Available in a unique 1.5 x 4 trapezoid shape
  - Available in six luminescent color blends

### MOSAIC

#### USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



MX  
MIXED MATERIALS



SEE CHARTS FOR FULL PRODUCT DETAILS

### SPECIAL FEATURES

Cover and above photos feature Regal Pendant™ Duchess Gold mosaic on the backsplash.

SIZES:



FINISHES: SATIN | GLOSSY

1-1/2 x 4 MOSAIC



CZARINA ICE RP09



CONTESSA CHARM RP11



AURELIAN EMPRESS RP12



DUCHESS GOLD RP10



PHARAOH ONYX RP08



BARONESS BIJOU RP07



SIMPLICLEAN™

## SIZES

	Thickness	Sq. Ft./ Carton	Pieces/ Carton
 1-1/2 x 4 Mosaic (Mesh-mounted on 12" x 11" Sheet)	3/8"	10.01	11
(11-7/8" x 11" Sheet) (30.10 cm x 27.90 cm Sheet)			

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

## APPLICATION NOTES:

For interior use only.

Suitable for interior wet applications such as shower wall or tub surround.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	 Random (V4)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## NOTES

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Use of a white latex modified thin-set is recommended for installation.

Stone is sealed at the factory and should be resealed regularly as part of normal maintenance.