



WALL

RELICCA™

GLAZED CERAMIC WALL AND MOSAIC TILE



 daltile®

RELICCA™

GLAZED CERAMIC WALL AND MOSAIC TILE

Relicca invites you to step into a classic, reimagined in contemporary style. Inspired by inherited collectibles, this series draws on vintage elements, while looking to the future with modern sizes and new 3D textures. Handcrafted wall options are complemented by a classic octagon and dot mosaic, for installations from the backsplash to the floor. With an artisanal look and a heritage of exceptional quality, Relicca is the heirloom of the future, leaving a legacy with a timeless look.

WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



REVEAL SYNC3D™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



GLAZED CERAMIC



LOW HIGH

SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.



Cover photo features Pristine, 4 x 4 Handcrafted on the wall.
Above photo features Unbound, Nook, and Foxed, 4 x 4 Handcrafted on the wall.

SIZES:



4 x 16 Handcrafted Wall Tile



4 x 4 Handcrafted Wall Tile



4 x 4 Circle Wall Tile



Octagon Dot Mosaic Tile

FINISHES: GLOSSY | MIXED

COLOR PALETTE




PRISTINE




DECKLE



UNBOUND



NOOK



ANTIQUE



FOXED

4 x 16 HANDCRAFTED WALL TILE



PRISTINE RA01



DECKLE RA02



UNBOUND RA03



NOOK RA04



ANTIQUE RA05



FOXED RA06

4 x 4 HANDCRAFTED WALL TILE



PRISTINE RA01



DECKLE RA02



UNBOUND RA03



NOOK RA04



ANTIQUE RA05



FOXED RA06

4 x 4 CIRCLE WALL TILE




PRISTINE RA01




DECKLE RA02




UNBOUND RA03



NOOK RA04




ANTIQUE RA05



FOXED RA06


OCTAGON DOT MOSAIC TILE




PRISTINE RA01



DECKLE RA02



UNBOUND RA03




NOOK RA04




ANTIQUE RA05



FOXED RA06



PRISTINE NOOK RA07



PRISTINE FOXED RA08



SLIP RESISTANT



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes









FIRE-RESISTANT



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

| | | | Thickness | Finish | Made in U.S.A. |
|--|---------------------------------------|--|-----------|-----------|---|
|  | 4 x 16 Handcrafted Wall Tile | 4" x 16" (10.18 cm x 40.69 cm) | 5/16" | G | |
|  | 4 x 4 Handcrafted Wall Tile | 4-1/4" x 4-1/4" (10.89 cm x 10.89 cm) | 5/16" | G |  |
|  | 4 x 4 Circle Wall Tile | 4-1/4" x 4-1/4" (10.89 cm x 10.89 cm) | 5/16" | G |  |
|  | Octagon Dot Mosaic Tile (Dot-Mounted) | 12" x 12" Sheet (30.48 cm x 30.48 cm Sheet) | 1/4" | MX | |

Made in the U.S.A. designation is subject to change. Please visit daltile.com for the most current manufacturing information.

G Glossy Finish **MX** Mixed Finish

APPLICATIONS

| | Target DCOF wet | Suitable |
|--|-----------------|----------|
| Dry & Level – Interior Floor | N/A | ✓* |
| Wet & Level – Interior Floor | ≥ 0.42 | ✓* |
| Shower Floors – Standard Center Drain | ≥ 0.42 | ✓* |
| Shower Floors – Linear Drain | ≥ 0.42 (Mosaic) | ✓* |
| | ≥ 0.60 (Floor) | |
| Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear) | ≥ 0.60 | |
| Ramps & Inclines | ≥ 0.65 | |
| Walls/Backsplashes | N/A | ✓ |
| Countertops | N/A | ✓* |
| Pool Linings | N/A | ✓** |


A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Wall and mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) non-freezing climates, when proper installation methods are followed.

* Mosaic tile only.
** Mosaic and 4 x 4 tile only

TRIM

| | Type | Number | Size | Finish |
|--|-------|---------|----------|----------|
|  | Jolly | S1/212J | 1/2 x 12 | G |

G Glossy Finish

INSTALLATION

| Grout Joint Recommendation | Shade Variation |
|----------------------------|-----------------|
|----------------------------|-----------------|

4 x 16 Wall Tile: 1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)



4 x 4 Wall Tile: 1/16"

Mosaic Tile: 1/8"

PERFORMANCE CHARACTERISTICS

| | ASTM# | Wall Result | Mosaic Result |
|---------------------|-------|-------------|---------------|
| Water Absorption | C373 | < 20.0% | < 3.0% |
| Breaking Strength | C648 | ≥ 125 lbf | > 250 lbf |
| Scratch Hardness | C1895 | ≥ 4.0 | 7.0 |
| Chemical Resistance | C650 | Resistant | Resistant |

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

| | | | |
|---|-----------------------|---|------------------------------------|
| 1 | Residential Bathrooms | 3 | All Residential / Light Commercial |
| 2 | All Residential Areas | ④ | All Residential / Commercial |

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



ZEROTOX

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



©2026 Daltile (1/26)