



CONCRETE LOOK

REMINISCENT™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ & GLAZED CERAMIC MOSAIC



REMINISCENT™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ & GLAZED CERAMIC MOSAIC

Embrace A Sleek Cement Look

The Reminiscent™ floor collection offers an updated approach to smooth cement and stone visuals. Perfect for both indoor and outdoor spaces, Reminiscent offers special installation flexibility. Utilizing Stepwise™ technology for increased traction, the collection features an unpolished finish and a heightened three-dimensional effect. With a modular floor tile size and a pressed ceramic mosaic, Reminiscent comes in timeless neutral hues.

- INSTALLATION FLEXIBILITY
 - Crafted from ColorBody™ porcelain and coordinating ceramic mosaic for a 3D visual
 - Floor tile with StepWise™ technology is suitable for exterior applications
- VERSATILE SELECTIONS
 - 12 x 24 floor tile and a 2 x 2 mosaic
 - Featured in four neutral colors

CONCRETE LOOK

USAGE



SPECIAL FEATURES

SEE CHARTS FOR FULL PRODUCT DETAILS

Photo features Reminiscent™ Aged Beige 12 x 24 on the floor.

SIZES:



12 x 24
Floor Tile



2 x 2
Mosaic

FINISHES: MATTE

COLOR PALETTE



MEMENTO
WHITE



AGED
BEIGE



SOUVENIR
GRAY



RECLAIMED
GRAY

COLORBODY™ PORCELAIN FLOOR TILE



MEMENTO WHITE RM20



AGED BEIGE RM21



SOUVENIR GRAY RM22



RECLAIMED GRAY RM23

2 X 2 GLAZED CERAMIC MOSAIC



MEMENTO WHITE RM20



AGED BEIGE RM21



SOUVENIR GRAY RM22



RECLAIMED GRAY RM23

50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*

*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

REMINISCENT™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ & GLAZED CERAMIC MOSAIC

CONCRETE LOOK



ALL STYLE. NO SLIPS.

Don't tip-toe through life. Step stylishly on non-slip tile that's 50% more slip resistant than ordinary tile. And because it's Daltile, you'll find beautiful natural looks that are waterproof, scratchproof, stainproof and dentproof.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 24" Floor Tile	(11-13/16" x 23-13/16") (30.00 cm x 60.48 cm)	5/16"	1760	9
	2 x 2 Mosaic (Dot-mounted on 12" x 24" Sheet)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12

* Floor tile featuring StepWise™ Technology. For more information, visit daltile.com/StepWise.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓**
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Mosaics are also suitable for residential and light commercial shower floors.

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* Mosaic tile only.

** 12 x 24 floor tile with Stepwise™ technology only.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



TRIM

Type	Number	Size	Pieces/ Carton
	P-43C9	3 x 12	30
	P-36C9TB	6 x 12	22
	PC-36C9TB	1 x 6	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

Cove base and cove corner trim are suitable for non-freezing climates only.

INSTALLATION

Grout Joint Recommendation

Shade Variation

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



Mosaic: 1/8"

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 3.0%
Breaking Strength	C648	> 275 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.