

STONE LOOK

XTERIORS™

ALL-WEATHER SOLUTIONS FOR EXTERIOR STYLE

BY  daltile®

ASSEMBLE™

COLORBODY™ PORCELAIN PAVERS

TREAD™
PORCELAIN PAVERS

ASSEMBLE™

COLORBODY™ PORCELAIN PAVERS

Gather Up Glamour

With Assemble™, every piece comes together to create the perfect design. This collection is comprised of unique stone-look visuals with the unsurpassed durability of 2CM porcelain tile paver. Offered in large-format sizes and grey tones, Assemble provides a contemporary and modern expression to your outdoor space.

- DIMENSIONAL DEPTH
 - This stone look combines terrazzo, an agglomerated visual, to the beauty of Natural Stone
 - Versatile random colors pair well with outdoor features, residential patios and commercial landscaping
- SEAMLESS DESIGN
 - Large-format size in 32 x 32 generates an uninterrupted, large-scale look
 - Coordinating 3/8" tiles integrate the indoors with the outdoors

STONE LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PC

LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS


SPECIAL FEATURES

SIZES:




FINISHES: TEXTURED


COLOR PALETTE




PROXY




MAGISTRATE




EMISSARY



PROXY AS10



MAGISTRATE AS11



EMISSARY AS12



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT




INDOOR/OUTDOOR








SIMPLICLEAN™

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	32 x 32 Paver Tile	(31-5/16" x 31-5/16") (79.50 cm x 79.50 cm)	13/16" (2cm)	6.89	1

TRIM†

	Type	Notes
	Rectified Step Nose	
	Coping	
	Rectified Gutter	† Trim items available in many sizes and colors. Consult with your sales representative and/or design team for specifics.
	Rectified Grid	
	Rectified L-Kerb	

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Dry Laying on Grass:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Dry Laying on Gravel:	Gaps of at least 3/16" (4 mm) should be left between slabs, using spacers to set the correct width. Joint may be left empty or filled with fine sand, polymeric sand specifically formulated for porcelain tile or small, clean aggregate, depending on the joint width and desired aesthetic.
Dry Laying on Sand:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Laying on Screed with Adhesive:	Slabs must be laid with open joints of variable width of no less than 3/16" (5 mm).
Raised Pavings:	Pedestal contains correct tile spacers for application.

SHADE VARIATION

AS10, AS11, AS12  Random (V4) - Considerable Variation from Tile to Tile

PERFORMANCE CHARACTERISTICS

	ASTM#	Paver Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 1000 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.

