

STONE LOOK

XTERIORS™

ALL-WEATHER SOLUTIONS FOR EXTERIOR STYLE

BY  daltile®

HADDONSTONE™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

TREAD™

PORCELAIN PAVERS

HADDONSTONE™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

Navigate the natural appeal of Haddonstone, a ColorBody™ porcelain series inspired by the organic look of Portland stone. Haddonstone offers a raw crosscut option that exudes a naturalistic aesthetic. The 2CM paver and coordinating mosaic tile, enhanced by StepWise™ technology offer endless indoor and outdoor possibilities.

STONE LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER
FLOOR



EXTERIOR
FLOOR



STEPWISE™



TRU-EDGE™



REVEAL
SYNC3D™



MADE IN
THE U.S.A.



LARGE
FORMAT



MOSAIC/
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



PC

LOW HIGH

NOT APPLICABLE
FOR ALL PRODUCTS
IN THIS SERIES. SEE
CHARTS FOR FULL
PRODUCT DETAILS.

SPECIAL FEATURES



Cover features Xteriors™ Haddonstone™ Dawn, 24 x 24 paver on the floor.

Above photo features Haddonstone™ Dawn and Atlas, 24 x 24 in a Diamond Grid pattern on the floor, Panoramic Porcelain Surfaces™ Smoked Geode on the cladding and Pebble Oasis™ Seashell, Pebble Mosaic in the pool.

STONE LOOK

HADDONSTONE™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

SIZES:



24 x 24
Paver Tile



2 x 2
Mosaic Tile

FINISHES: MATTE | TEXTURED

COLORBODY™ PORCELAIN PAVERS



PEONY HS04



DAWN HS05



ATLAS HS06

2 X 2 MOSAIC TILE WITH STEPWISE™ TECHNOLOGY



PEONY HS04



DAWN HS05



ATLAS HS06

50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT*
*Not Applicable to Mesh-Mounted
Mosaics








INDOOR/OUTDOOR



SIMPLICLEAN™



VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Finish	Made in U.S.A.
	24 x 24 Crosscut Paver Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	13/16"		
	2 x 2 Crosscut Mosaic Tile (Mesh-mounted)	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	5/16"		

 Matte Finish  Textured Finish

TRIM†

	Type
	Step Nose Tile
	Coping Tile

† Trim items available in many sizes and colors. Consult with your sales representative and/or design team for specifics.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors – Standard Center Drain	≥ 0.42	✓*
Shower Floors – Linear Drain	≥ 0.60 (Mosaic)	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

*Mosaic tile only.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.



INSTALLATION

Dry Laying on Grass:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Dry Laying on Gravel:	Gaps of at least 3/16" (5 mm) should be left between slabs, using spacers to set the correct width. Joint may be left empty or filled with fine sand, polymeric sand specifically formulated for porcelain tile or small, clean aggregate, depending on the joint width and desired aesthetic.
Dry Laying on Sand:	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
Laying on Screed with Adhesive:	Slabs must be laid with open joints of variable width of no less than 3/16" (5 mm).
Raised Pavings:	Pedestal contains correct tile spacers for application.
Mosaic:	1/8"

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

	ASTM#	Mosaic Result	Paver Result
Water Absorption	C373	< 0.5%	< 0.5%
Breaking Strength	C648 C1505	> 275 lbf N/A	N/A ≥ 2000 lbf
Scratch Hardness	C1895	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	N/A	N/A

For additional information on test results, visit us at: daltille.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors,

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at daltille.com.

