

CONCRETE LOOK

# XTERIORS™

ALL-WEATHER SOLUTIONS FOR EXTERIOR STYLE

BY  daltile



NOMINEE™

COLORBODY™ PORCELAIN PAVERS

TREAD™

PORCELAIN PAVERS

# NOMINEE™

COLORBODY™ PORCELAIN PAVERS

## Stylish Refinement

With concrete look porcelain pavers from Daltile, you can combine style and performance with unsurpassed durability. Daltile's TREAD™ collection of pavers offers Nominee™ which brings the fashionable look of concrete to your outdoor living environment. Our outdoor pavers offer design solutions with character, strength and a sophisticated, contemporary appeal for any project.

- EXTERIOR SOLUTION
  - Concrete look outdoor paver
  - Three distinct colors complete any outdoor space
- UNIVERSAL DESIGN
  - Versatile 24 x 24 paver tile can be used in a variety of outdoor settings
  - Complement your indoor concrete look tile with the durability of porcelain pavers

### CONCRETE LOOK

#### USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PC

LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

### SPECIAL FEATURES

Cover photo features Nominee™ Sand in 24x24.  
Above photo features Nominee™ Grey in 24x24.

SIZES:



FINISHES: MATTE

COLOR PALETTE



SAND



TAUPE



GREY



SAND NM10



TAUPE NM11



GREY NM12



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



INDOOR/OUTDOOR




SIMPLICLEAN™

# NOMINEE™






COLORBODY™ PORCELAIN PAVERS

CONCRETE LOOK

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Paver Tile	(23-1/2" x 23-1/2") (59.70 cm x 59.70 cm)	13/16" (2cm)	7.67	2

## TRIM†

	Type	Notes
	Rectified Step Nose	
	Coping	
	Rectified Gutter	† Trim items available in many sizes and colors. Consult with your sales representative and/or design team for specifics.
	Rectified Grid	
	Rectified L-Kerb	

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltil.com/DCOF](http://daltil.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

## INSTALLATION

<b>Dry Laying on Grass:</b>	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
<b>Dry Laying on Gravel:</b>	Gaps of at least 3/16" (4 mm) should be left between slabs, using spacers to set the correct width. Joint may be left empty or filled with fine sand, polymeric sand specifically formulated for porcelain tile or small, clean aggregate, depending on the joint width and desired aesthetic.
<b>Dry Laying on Sand:</b>	The gaps between the slabs should be chosen depending on the overall desired aesthetic.
<b>Laying on Screed with Adhesive:</b>	Slabs must be laid with open joints of variable width of no less than 3/16" (5 mm).
<b>Raised Pavings:</b>	Pedestal contains correct tile spacers for application.

## SHADE VARIATION

NM10, NM11, NM12  Medium (V2)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Paver Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 1000 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: [daltil.com/information/TestResults](http://daltil.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: [daltil.com/Factors](http://daltil.com/Factors).

## PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltil.com](http://daltil.com).

