



STONE LOOK

SCRIPTER™
GLAZED PORCELAIN with STEPWISE™

 **daltile®**
IMAGINE WHAT'S POSSIBLE™

SCRIPTER™

GLAZED PORCELAIN with STEPWISE™

Storytelling Style

Scripter™ embarks on a storytelling design journey. This neutral, stone look comes in large format sizes and an 8" hexagon floor tile. Designed to complement the entire color palette, the 8" hexagon decorative accent can be used on its own or combined with any of the four solid colors, for a unique design touch. The entire collection features StepWise™ technology allowing your design to extend outdoors. From beginning to end, Scripter conquers your ideal design desires.

- CAST OF CHARACTERS
 - 12 x 24, 24 x 24 and 8" hexagon in four stone look colors
 - 8" hexagon decorative accent coordinates with entire color palette
- ADVENTURE ANYWHERE
 - Quintessential journey to conquer design trends
 - StepWise™ technology offers a high level of slip resistance, perfect for indoor/outdoor applications

STONE LOOK

USAGE



SPECIAL FEATURES

Cover photo features Scripter™ Rebel 8" hexagon matte on the wall, Scripter™ Rebel 24 x 24 matte on the floor and ONE Quartz Surfaces® Valor White polished on the counter.

Above photo features Scripter™ Hero 12 x 24 matte on the floor, Commissary™ Regent Honey 24 x 24 paver tile on the pool surround, Remedy™ Hydro 2 x 9 glossy on the side wall, Panoramic Porcelain Surfaces™ Anthracite glossy on the back wall and Panoramic Porcelain Surfaces™ Calacatta matte on the back counter.

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

SCRIPTER™

GLAZED PORCELAIN with STEPWISE™

SIZES:



24 x 24
Floor Tile



12 x 24
Floor Tile



8" Hexagon
Floor Tile



8" Hexagon
Decorative
Accent

FINISHES: MATTE

COLOR PALETTE



ORACLE



HERO



MENTOR



REBEL

FLOOR TILE



ORACLE AR60



HERO AR61




MENTOR AR62




REBEL AR63

8" HEXAGON FLOOR TILE




ORACLE AR60



HERO AR61



MENTOR AR62



REBEL AR63

8" HEXAGON DECORATIVE ACCENT



QUEST AR64

50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SCRIPTER™

GLAZED PORCELAIN with STEPWISE™

STONE LOOK



ALL STYLE. NO SLIPS.

Don't tip-toe through life. Step stylishly on non-slip tile that's 50% more slip resistant than ordinary tile. And because it's Daltile, you'll find beautiful natural looks that are waterproof, scratchproof, stainproof and dentproof.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Floor Tile	(23-13/16" x 23-13/16") (60.48 cm x 60.48 cm)	5/16"	15.76	4
	12 x 24 Floor Tile	(11-13/16" x 23-13/16") (30.00 cm x 60.48 cm)	5/16"	15.60	8
	8" Hexagon Floor Tile	(7-7/8" x 9-1/8") (20.04 cm x 23.16 cm)	5/16"	9.37	25
	8" Hexagon Decorative Accent	(7-7/8" x 9-1/8") (20.04 cm x 23.16 cm)	5/16"	9.37	25

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

TRIM

Type	Number	Size	Pieces/ Carton
Bullnose	P43F9	3 x 24	10

INSTALLATION

Grout Joint Recommendation	Shade Variation
----------------------------	-----------------

3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltile.com.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

