



STONE LOOK

SCRIPTER™

GLAZED PORCELAIN with STEPWISE™ TECHNOLOGY


 daltile®  
IMAGINE WHAT'S POSSIBLE™

# SCRIPTER™

GLAZED PORCELAIN with STEPWISE™ TECHNOLOGY

## Storytelling Style

Scripter™ embarks on a storytelling design journey. This neutral, stone look comes in large format sizes and an 8" hexagon floor tile. Designed to complement the entire color palette, the 8" hexagon decorative accent can be used on its own or combined with any of the four solid colors, for a unique design touch. The entire collection features StepWise™ technology allowing your design to extend outdoors. From beginning to end, Scripter conquers your ideal design desires.



Cover photo features Scripter™ Rebel 8" hexagon matte on the wall, Rebel 24 x 24 matte on the floor and ONE Quartz Surfaces® Valor White polished on the counter.

Above photo features Scripter™ Hero 12 x 24 matte on the floor, Commissary™ Regent Honey 24 x 24 paver tile on the pool surround, Remedy™ Hydro 2 x 9 glossy on the side wall, Panoramic Porcelain Surfaces™ Anthracite glossy on the back wall and Panoramic Porcelain Surfaces™ Calacatta matte on the back counter.

### STONE LOOK

### USAGE



### SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

# STONE LOOK

# SCRIPTER™

GLAZED PORCELAIN with STEPWISE™ TECHNOLOGY

### SIZES:



24 x 24  
Floor Tile



12 x 24  
Floor Tile



8" Hexagon  
Floor Tile



8" Hexagon  
Decorative  
Accent

FINISHES: MATTE

### COLOR PALETTE



ORACLE



HERO



MENTOR



REBEL

### FLOOR TILE



ORACLE AR60



HERO AR61




MENTOR AR62




REBEL AR63

### 8" HEXAGON FLOOR TILE




ORACLE AR60



HERO AR61



MENTOR AR62



REBEL AR63

### 8" HEXAGON DECORATIVE ACCENT



QUEST AR64

**50% MORE**  
SLIP RESISTANT  
THAN ORDINARY TILE\*

\*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



INDOOR/OUTDOOR



SIMPLICLEAN™











VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

# SCRIPTER™

GLAZED PORCELAIN with STEPWISE™ TECHNOLOGY

STONE LOOK

## SIZES

			Thickness	Finish	Made in U.S.A
	24 x 24 Floor Tile	23-13/16" x 23-13/16" (60.48 cm x 60.48 cm)	5/16"		
	12 x 24 Floor Tile	11-13/16" x 23-13/16" (30.00 cm x 60.48 cm)	5/16"		
	8" Hexagon Floor Tile	7-7/8" x 9-1/16" (19.95 cm x 23.04 cm)	5/16"		
	8" Hexagon Decorative Accent	7-7/8" x 9-1/16" (19.95 cm x 23.04 cm)	5/16"		

 Matte Finish

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic)	
	≥ 0.60 (Floor)	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	



A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

\*12 x 24 floor tile only.

## TRIM

Type	Number	Size	Finish
 Bullnose	P43F9	3 x 24	

 Matte Finish

## INSTALLATION

### Grout Joint Recommendation

### Shade Variation

3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)

 Medium (V2)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A1371 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [daltile.com](http://daltile.com).

 PRE-CONSUMER RECYCLED MATERIALS

 POST-CONSUMER RECYCLED MATERIALS

 REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).

CERTIFIED  
**PORCELAIN**  
TILE  
0.0% or less water absorption



**ZEROTOX**

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).

 **daltile**  
IMAGINE WHAT'S POSSIBLE™

©2025 Daltile (04/25)